



JOHNSONITE RESILIENT MOULDINGS

Subfloor Leveler System

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Leveler Strip and Leveler Strip

1.2. **Manufacturer:**

| | |
|--|-----------------------|
| Tarkett | Phone: (800) 899-8916 |
| 30000 Aurora Rd. | (440) 543-8916 |
| Solon, Ohio 44139 | Tech: Ext 9297 |
| Web: www.tarkettna.com | Samples: Ext 9299 |
| E-mail: info@johnsonite.com | |

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Johnsonite Resilient Leveler Strips are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. The Leveler Strip complies with A.D.A. requirements for change of level and exceeds the slope to rise ratio for Ramps. The formulation exceeds ASTM E 648 Class 1 Flammability requirements. Johnsonite Leveler Strips are designed for interior applications only

1.3.2. **Styles:**

LS-40: 1/4" (6.35 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-B: 3/8" (9.53 mm) to 1/4" (6.35 mm) butt-to reducer tapering across a 6" (15.24 cm) width, extends LS-40 from 1/4" (6.35 mm) to 3/8" (9.53 mm) thickness, increases taper from 12" (30.48 cm) to 18" (45.72 cm)

LS-40-C: 1/2" (12.7 mm) to 3/8" (9.53 mm) butt-to reducer tapering across a 6" (15.24 cm) width. Note: Extends LS-40 with LS-40-B extension from 3/8" (9.53 mm) to 1/2" (12.7 mm) thickness. Increases taper from 18" (45.72 cm) to 24" (60.96 cm).

LS-40-D: 3/8" (9.53 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-E: 1/2" (12.7 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-F: 1/8" (3.175 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-G: 3/4" (19.05 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-K: 1/4" (6.35 mm) to substrate butt-to reducer with 1-3/4" (4.4 cm) flat mounting surface for tack strip installation, 12" (30.48 cm) width, tapered across 10-1/4" (26 cm)

1.3.3. **Physical Characteristics:**

Length: 4 ft. (1.22 m)

Packaging:

| | |
|-----------|---|
| LS-40 | 10 pcs / carton, 40 ft (12.2 m) - 55 lbs (25 kg)/ctn |
| LS-40 - B | 8 pcs / carton, 32 ft (9.75 m) - 46 lbs. (21 kg)/ctn |
| LS-40 - C | 6 pcs / carton, 24 ft (7.32 m) - 45 lbs. (20 kg)/ctn |
| LS-40 - D | 5 pcs / carton, 20 ft (6.10 m) - 42 lbs. (19 kg)/ctn |
| LS-40 - E | 5 pcs / carton, 20 ft. (6.10 m) - 59 lbs. (27 kg)/ctn |
| LS-40 - F | 20 pcs / carton, 80 ft (24.4 m) - 40 lbs. (18 kg)/ctn |
| LS-40 - G | 4 pcs / carton, 16 ft (4.88 m) - 54 lbs. (25 kg)/ctn |
| LS-40 - K | 10 pcs / carton, 40 ft (12.2 m) - 46 lbs. (21 kg)/ctn |

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1. See Johnsonite Subfloor Leveler System installation instructions for complete details.

3.2. **Adhesives:**

• **Tarkett 925 Adhesive:**

Coverage:

Porous Substrate: 250-300 sq. ft./gal.

Non-porous Substrate: 250-300 sq. ft. per gallon

• **Tarkett 965 Adhesive Coverage:**

Porous Substrate: 125-150 sq. ft. per gallon

Non-porous Substrate: 150-175 sq. ft. per gallon

• **Tarkett 901 SpraySmart Adhesive Coverage:**

Porous & Non-porous Substrate: 80 sq. ft. per can (480 sq. ft. per carton)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

N/A

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



Technical Services Department
 30000 Aurora Road, Solon, Ohio 44139
 (800) 899-8916 ext 9297
 Fax (440) 632-5643
 email: info@johnsonite.com
www.tarkettna.com