

PLAY

WOOD - PRODUCT DATASHEET 2020



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1 (when applicable) / EN 13501	Dfl-s1*
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Ash Oak	(BHN) EN1534	4,0 3,7
Taber Abraser/Lacquer's wear resistance Proteco Natura <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	N/A
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K) 13 mm 14 mm	EN 12664 / EN 14342:2013	0,104 0,11
Construction	3-layer with softwood core	
* Cfl-s1 for lacquered products can be provided on demand.		

INSTALLATION		
Installation method	2-lock for floating or glue down	
Installation instruction	Download from www.tarkett.com Contact your supplier for more details	
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes	
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m²		

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

DIMENSIONS & PACKAGE	13x162x2000	14x162x2000
Thickness EN 13489 (mm)	13	14
Width (mm)	162	162
Length (mm)	2000	2000
Wear layer thickness (mm)	2,5	3,5
Boards/pack	6	6
m ² /pack	1,94	1,94
m ² /pallet	69,84	69,84
Net weight/m ² (kg)	7,3	7,9

DIMENSIONS & PACKAGE	14x162x2200	14x162x2520
Thickness EN 13489 (mm)	14	14
Width (mm)	162	162
Length (mm)	2200	2520
Wear layer thickness (mm)	3,5	3,5
Boards/pack	6	6
m ² /pack	2,14	2,45
m ² /pallet	77,04	88,20
Net weight/m ² (kg)	7,9	7,9

Due to the nature of the material this table shows typical values.

MAINTENANCE
These Tarkett wooden floors have a Proteco treatment and therefore a strong protection against wear, abrasion, scratches and stains. However, because of their very nature some floors will require more frequent maintenance for increased life span; light coloured floors, Hardwax oiled floors, brushed floors, floors with saw marks.
See maintenance instructions @ www.tarkett.com

Play 14 mm Proteco Natura Play 13 mm Proteco Natura



2-LOCK



Tarkett

PLAY


WOOD - PRODUCT DATASHEET 2020

DESIGN

A collection of floors that highlights the quality of the wood through new and experimental effects on its surface, giving every board a touch of the extraordinary.

PRODUCT DATA	Material code	Dimensions L x W x H (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Stained	Latin name	DoP no.
Play Ash Ivory Plank	41006008	2 000 x 162 x 13	1-strip	Proteco Natura	-	Minibevel	Yes	1	0190-0103
Play Oak Winter Plank	7876007	2 000 x 162 x 14	1-strip	Proteco Natura	Brushed	Handmade bevel	Yes	2	0190-0105
	7876024	2 520 x 162 x 14	1-strip	Proteco Natura	Brushed	Handmade bevel	Yes	2	0190-0105
Play Oak Marble Plank	7876009	2 200 x 162 x 14	1-strip	Proteco Natura	Brushed	Minibevel	Yes	3	0190-0105
Play Oak Charcoal Plank	7876106	2 000 x 162 x 14	1-strip	Proteco Natura	Brushed	Minibevel	Yes	3	0190-0105

1: Fraxinus Angustifolia, 2: Quercus Alba , 3: Quercus Robur & Quercus Petraea



Play Ash Ivory Plank



Play Oak Winter Plank



Play Oak Marble Plank



Play Oak Charcoal Plank

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com