

SPECIALS

PRODUCT DATASHEET 2018


TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1 (when applicable) / EN 13501	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Proteco Natura / Proteco Hardwax Oil <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	N/A
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K) 13 mm	EN 12664 / EN 14342:2013	0,104

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

DIMENSIONS & PACKAGE	13x155x1850	13x194x2281
Thickness EN 13489 (mm)	13	13
Width (mm)	155	194
Length (mm)	1850	2281
Wear layer thickness (mm)	2,5	2,5
Boards/pack	6	6
m ² /pack	1,72	2,66
m ² /pallet	72,24	106,4
Net weight/m ² (kg)	7,3	7,3

MAINTENANCE
These Tarkett wooden floors have a Proteco treatment and therefore a strong protection against wear, abrasion, scratches and stains. However, because of their very nature some floors will require more frequent maintenance for increased life span; Light coloured floors, Hardwax oiled floors, brushed floors, floors with saw marks.
See maintenance instructions @ www.tarkett.com



WOOD

SPECIALS

PRODUCT DATA	Material code	Dimensions (mm)			Pattern	Surface treatment	Surface effect	Bevel	Stained	DoP no.
		Thickness	Width	Length						
Oak Super Rustic Plank White	41017901	13	155	1 850	1-strip	Proteco Hardwax Oil	Deep brushed	2 side minibevel	Yes	0190-0103
Oak Nature White DuoPlank	8727902	13	194	2 281	2-strip	Proteco Natura	-	-	Yes	0020-0104



Oak Super Rustic Plank White



Oak Nature White DuoPlank

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.

For further and latest information please visit www.tarkett.com