



TILE + PLANK

VENUE SERIES
VENUE ABSTRACT (UVA)

Tandus Centiva


A Tarkett Company

SPECIFICATIONS

Classification: ASTM F1700 Class III Type B
Total Thickness: 0.120" (3.0 mm)
Wear Layer Thickness: 20 mil (0.5 mm)
Edge Treatment: Square (SE)
Emboss: Standard
 Quarry (QU) (Concrete, Criss Cross)
 Linear Wood (LW) (Fine Lines, Tread)

Warranty: 10-Year Limited Commercial Wear Warranty
Colors: 21
Adhesive: CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:
 Product specific.
 Please see tandus-centiva.com for more information.



Product shown: UVA 5103

SIZES				
Concrete	18" x 18" (45.72 cm x 45.72 cm)	Criss Cross	18" x 18" (45.72 cm x 45.72 cm)	Fine Lines & Tread
	36" x 36" (91.44 cm x 91.44 cm)		36" x 36" (91.44 cm x 91.44 cm)	18" x 18" (45.72 cm x 45.72 cm)
	6" x 36" (15.24 cm x 91.44 cm)			6" x 36" (15.24 cm x 91.44 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF ≥ 0.45 watts/cm ² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^{MC}
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Recycled Content: 30% Preconsumer
Materials: No Heavy Metals; Non-Toluene Ink System
Indoor Air Quality: Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
Recyclability: 100% Recyclable through our ReStart® Program
LEED Scoreboard: LEED 2009
 MRc2 Construction Waste Management
 MRc4 Recycled Content
 MRc5 Regional Materials
 IEQ 4.1 Low-Emitting Adhesives
 IEQ 4.3 Low-Emitting Materials Flooring
Manufacturing: Made in the USA
 ISO 9001 Quality Management System
 ISO 14001 Environmental Management System
 OHSAS 18001 Occupational Health and Safety Management System
Third-party Certification: NSF/ANSI-332 Silver
Packaging: Packaged in recycled, corrugated cardboard

QUICKSHIP PROGRAM

Q All Venue Series products
QE Select colors available
 LEED v4
 MRc2 Building Product Disclosure and Optimization – Environmental Product Declarations
 MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
 MRc5 Construction and Demolition Waste Management
 IEQc2 Low-Emitting Materials

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/IEL NSF 332