



TILE + PLANK

VENUE SERIES
VENUE STONE (UVS)

Tandus Centiva

A Tarkett Company

SPECIFICATIONS

Classification: ASTM F1700 Class III Type B

Total Thickness: 0.120" (3.0 mm)

Wear Layer Thickness: 20 mil (0.5 mm)

Edge Treatment: Square (SE)


Emboss: Standard
Quarry (QU) (all but Slate products, see below)
Slate (SL) (SL61, SL64, SL65, SL72, SL78 only)

Warranty: 10-Year Limited Commercial Wear Warranty

Colors: 12

Adhesive: CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:



Product shown: UVS 7240

SIZES

12" x 24" (30.48 cm x 60.96 cm)
18" x 18" (45.72 cm x 45.72 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF≥0.45 watts/cm ² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^{MC}
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Recycled Content: 30% Preconsumer

Materials: No Heavy Metals;
Non-Toluene Ink System

Indoor Air Quality: Meets CDPH Standard Method v1.1-2010;
FloorScore® Certification

Recyclability: 100% Recyclable through our ReStart® Program

LEED Scoreboard: LEED 2009
MRc2 Construction Waste Management
MRc4 Recycled Content
MRc5 Regional Materials
IEQ 4.1 Low-Emitting Adhesives
IEQ 4.3 Low-Emitting Materials Flooring

Manufacturing: Made in the USA
ISO 9001 Quality Management System
ISO 14001 Environmental Management System
OHSAS 18001 Occupational Health and Safety Management System

Third-party Certification NSF/ANSI-332 Silver

Packaging: Packaged in recycled, corrugated

QUICKSHIP PROGRAM

- All Venue Series products
- Select colors available

LEED v4
MRc2 Building Product Disclosure and Optimization – Environmental Product Declarations
MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
MRc5 Construction and Demolition Waste Management
IEQc2 Low-Emitting Materials



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL NSF 332

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.