



TILE + PLANK

VENUE SERIES
VENUE WOOD (UVP)


Tandus Centiva

A Tarkett Company

SPECIFICATIONS

Classification:	ASTM F1700 Class III Type B
Total Thickness:	0.120" (3.0 mm)
Wear Layer Thickness:	20 mil (0.5 mm)
Edge Treatment:	Square (SE)
Emboss:	Standard
<i>Product specific.</i>	Weathered Grain (WG)
<i>Please see tandus-centiva.com</i>	Linear Wood (LW)
<i>for more information.</i>	Cross Grain (CG)
Warranty:	10-Year Limited Commercial Wear Warranty
Colors:	25
Adhesive:	CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:



Product shown: UVP 3530

SIZES	4" x 36" (10.16 cm x 91.44 cm)
	6" x 36" (15.24 cm x 91.44 cm)
	6" x 48" (15.24 cm x 121.92 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF≥0.45 watts/cm² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^{MC}
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Recycled Content:	30% Preconsumer
Materials:	No Heavy Metals; Non-Toluene Ink System
Indoor Air Quality:	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
Recyclability:	100% Recyclable through our ReStart® Program
LEED Scoreboard:	LEED 2009 MRc2 Construction Waste Management MRc4 Recycled Content MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
Manufacturing:	Made in the USA ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System

Third-party Certification: NSF/ANSI-332 Silver

Packaging: Packaged in recycled, corrugated cardboard

QUICKSHIP PROGRAM



All Venue Series products



Select colors available

LEED v4

- MRc2 Building Product Disclosure and Optimization – Environmental Product Declarations
- MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
- MRc5 Construction and Demolition Waste Management
- IEQc2 Low-Emitting Materials



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/IEL NSF 332

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.