



TILE + PLANK

VICTORY SERIES
BRITES (VBR)

Tandus Centiva

A Tarkett Company

SPECIFICATIONS

Classification: ASTM F1700 Class I Type B
Total Thickness: 0.120" (3.0 mm)
Wear Layer Thickness: N/A, Solid vinyl tile
Edge Treatment: Square (SE) or Slight Bevel (SB)
Emboss: Standard:
Slate (SS)
Granite (JS) available

Warranty: 20-Year Limited Commercial Wear Warranty
Colors: 7
Adhesive: CENTI 2001 Wet Set, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:



SIZES

12" x 12" (30.48 cm x 30.48 cm)	12" x 36" (30.48 cm x 91.44 cm)
12" x 18" (30.48 cm x 45.72 cm)	18" x 18" (45.72 cm x 45.72 cm)
18" x 36" (45.72 cm x 91.44 cm)	6" x 36" (15.24 cm x 91.44 cm)
9" x 36" (22.86 cm x 91.44 cm)	36" x 36" (91.44 cm x 91.44 cm)

TESTING

Flexibility: ASTM F137	Passes
Dimensional Stability: ASTM F2199	Passes
Static Load: ASTM F970	Passes
Residual Indentation: ASTM F1914	Excellent
Flammability: ASTM E648	CRF ≥ 0.45 watts/cm ² NFPA Class 1
Slip Resistance: ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density: ASTM E662	Passes <450 D ^M C
Resistance to Light: ASTM F1515	Excellent
Chemical Resistance: ASTM F925	Excellent
Resistance to Heat: ASTM F1514	Excellent

ENVIRONMENTAL DATA

Materials: No Heavy Metals; Phthalate-free	
Indoor Air Quality: Meets CDPH Standard Method v1.1-2010; FloorScore® Certification	
Recyclability: 100% Recyclable through our ReStart® Program	
LEED Scoreboard: LEED 2009	LEED v4
MRC2 Construction Waste Management	MRC2 Building Product Disclosure and Optimization – Environmental Product Declarations
MRc5 Regional Materials	MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
IEQ 4.1 Low-Emitting Adhesives	MRc5 Construction and Demolition Waste Management
IEQ 4.3 Low-Emitting Materials Flooring	IEQc2 Low-Emitting Materials
Third-party Certification: NSF/ANSI-332 Gold	
Manufacturing: Made in the USA	
ISO 9001 Quality Management System	
ISO 14001 Environmental Management System	
OHSAS 18001 Occupational Health and Safety Management System	
Packaging: Packaged in recycled, corrugated cardboard	



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL NSF 332

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

VICTORY SERIES
CHROMA (VCM)


Tandus Centiva

A Tarkett Company

SPECIFICATIONS

Classification:	ASTM F1700 Class I Type B
Total Thickness:	0.120" (3.0 mm)
Wear Layer Thickness:	N/A, Solid vinyl tile
Edge Treatment:	Square (SE) or Slight Bevel (SB)
Emboss:	Standard: Slate (SS) Granite (JS) available
Warranty:	20-Year Limited Commercial Wear Warranty
Colors:	28
Adhesive:	CENTI 2001 Wet Set, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:



Products shown: VCM 0100, 0104, 0120, 0108

SIZES

12" x 12" (30.48 cm x 30.48 cm)	12" x 36" (30.48 cm x 91.44 cm)
12" x 18" (30.48 cm x 45.72 cm)	18" x 18" (45.72 cm x 45.72 cm)
18" x 36" (45.72 cm x 91.44 cm)	6" x 36" (15.24 cm x 91.44 cm)
9" x 36" (22.86 cm x 91.44 cm)	36" x 36" (91.44 cm x 91.44 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF ≥ 0.45 watts/cm ² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^M C
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Materials:	No Heavy Metals; Phthalate-free	
Indoor Air Quality:	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification	
Recyclability:	100% Recyclable through our ReStart® Program	
LEED Scoreboard:	LEED 2009	LEED v4
	MRC2 Construction Waste Management	MRC2 Building Product Disclosure and Optimization – Environmental Product Declarations
	MRC5 Regional Materials	MRC3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
	IEQ 4.1 Low-Emitting Adhesives	MRC5 Construction and Demolition Waste Management
	IEQ 4.3 Low-Emitting Materials Flooring	IEQc2 Low-Emitting Materials
Third-party Certification:	NSF/ANSI-332 Gold	
Manufacturing:	Made in the USA ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System	
Packaging:	Packaged in recycled, corrugated cardboard	



PRODUCT CERTIFIED
FOR REDUCED ENVI-
RONMENTAL IMPACT.
VIEW SPECIFIC ATTRI-
BUTES EVALUATED:
UL.COM/EL
NSF 332

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

VICTORY SERIES
CORAL REEF (VCR)


Tandus Centiva

A Tarkett Company

SPECIFICATIONS

Classification:	ASTM F1700 Class I Type B
Total Thickness:	0.120" (3.0 mm)
Wear Layer Thickness:	N/A, Solid vinyl tile
Edge Treatment:	Square (SE) or Slight Bevel (SB)
Emboss:	Standard: Slate (SS) Granite (JS) available
Warranty:	20-Year Limited Commercial Wear Warranty
Colors:	22
Adhesive:	CENTI 2001 Wet Set, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:



Product shown: VCR 0003

SIZES

12" x 12" (30.48 cm x 30.48 cm)	12" x 36" (30.48 cm x 91.44 cm)
12" x 18" (30.48 cm x 45.72 cm)	18" x 18" (45.72 cm x 45.72 cm)
18" x 36" (45.72 cm x 91.44 cm)	6" x 36" (15.24 cm x 91.44 cm)
9" x 36" (22.86 cm x 91.44 cm)	36" x 36" (91.44 cm x 91.44 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF ≥ 0.45 watts/cm ² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^M C
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Materials:	No Heavy Metals; Phthalate-free	
Indoor Air Quality:	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification	
Recyclability:	100% Recyclable through our ReStart® Program	
LEED Scoreboard:	LEED 2009	LEED v4
	MRC2 Construction Waste Management	MRC2 Building Product Disclosure and Optimization – Environmental Product Declarations
	MRc5 Regional Materials	MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
	IEQ 4.1 Low-Emitting Adhesives	MRc5 Construction and Demolition Waste Management
	IEQ 4.3 Low-Emitting Materials Flooring	IEQc2 Low-Emitting Materials
Third-party Certification:	NSF/ANSI-332 Gold	
Manufacturing:	Made in the USA ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System	
Packaging:	Packaged in recycled, corrugated cardboard	



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL NSF 332

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

VICTORY SERIES
MAGICS (VMG)


Tandus Centiva

A Tarkett Company

SPECIFICATIONS

Classification:	ASTM F1700 Class I Type B
Total Thickness:	0.120" (3.0 mm)
Wear Layer Thickness:	N/A, Solid vinyl tile
Edge Treatment:	Square (SE) or Slight Bevel (SB)
Emboss:	Standard: Slate (SS) Granite (JS) available
Warranty:	20-Year Limited Commercial Wear Warranty
Colors:	21
Adhesive:	CENTI 2001 Wet Set, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:



RANDOM



Product shown: VMG 8044

SIZES

12" x 12" (30.48 cm x 30.48 cm)	12" x 36" (30.48 cm x 91.44 cm)
12" x 18" (30.48 cm x 45.72 cm)	18" x 18" (45.72 cm x 45.72 cm)
18" x 36" (45.72 cm x 91.44 cm)	6" x 36" (15.24 cm x 91.44 cm)
9" x 36" (22.86 cm x 91.44 cm)	36" x 36" (91.44 cm x 91.44 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF ≥ 0.45 watts/cm ² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes > 0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes < 450 D ^M C
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Materials:	No Heavy Metals; Phthalate-free	
Indoor Air Quality:	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification	
Recyclability:	100% Recyclable through our ReStart® Program	
LEED Scoreboard:	LEED 2009	LEED v4
	MRC2 Construction Waste Management	MRC2 Building Product Disclosure and Optimization – Environmental Product Declarations
	MRC5 Regional Materials	MRC3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
	IEQ 4.1 Low-Emitting Adhesives	MRC5 Construction and Demolition Waste Management
	IEQ 4.3 Low-Emitting Materials Flooring	IEQc2 Low-Emitting Materials
Third-party Certification:	NSF/ANSI-332 Gold	
Manufacturing:	Made in the USA ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System	
Packaging:	Packaged in recycled, corrugated cardboard	



PRODUCT CERTIFIED
FOR REDUCED ENVI-
RONMENTAL IMPACT.
VIEW SPECIFIC ATTRI-
BUTES EVALUATED:
UL.COM/EL
NSF 332

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

VICTORY SERIES
MINERAL CHIP (VMN)

Tandus Centiva


A Tarkett Company

SPECIFICATIONS

Classification: ASTM F1700 Class I Type B
Total Thickness: 0.120" (3.0 mm)
Wear Layer Thickness: N/A, Solid vinyl tile
Edge Treatment: Square (SE) or Slight Bevel (SB)
Emboss: Standard
 Granite (JS)

Warranty: 20-Year Limited Commercial Wear Warranty
Colors: 6
Adhesive: CENTI 2001 Wet Set, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

Installation Methods:



RANDOM



SIZES

12" x 12" (30.48 cm x 30.48 cm)
 12" x 18" (30.48 cm x 45.72 cm)
 18" x 18" (45.72 cm x 45.72 cm)
 6" x 36" (15.24 cm x 91.44 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF ≥ 0.45 watts/cm ² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^M C
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Materials:	No Heavy Metals; Phthalate-free	
Indoor Air Quality:	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification	
Recyclability:	100% Recyclable through our ReStart® Program	
LEED Scoreboard:	LEED 2009	LEED v4
	MRC2 Construction Waste Management	MRC2 Building Product Disclosure and Optimization – Environmental Product Declarations
	MRC5 Regional Materials	MRC3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
	IEQ 4.1 Low-Emitting Adhesives	MRC5 Construction and Demolition Waste Management
	IEQ 4.3 Low-Emitting Materials Flooring	IEQc2 Low-Emitting Materials
Third-party Certification:	NSF/ANSI-332 Gold	
Manufacturing:	Made in the USA ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System	
Packaging:	Packaged in recycled, corrugated cardboard	



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/ELNSF332

- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.