

TECHNICAL DATA

CERTIFICATION & CLASSIFICATION	STANDARDS	iQ One
Type of floor covering	EN 14565	Homogeneous floor covering based upon synthetic thermoplastic polymers.
CE certification	EN 14041	Yes
ISO certification		Ronneby ISO 9001/ Ronneby ISO 14001
TECHNICAL CHARACTERISTICS	STANDARDS	iQ One
iQ PUR		Yes
Total thickness	ISO 24346 – EN 428	2.0 mm
Wear layer thickness	ISO 24340 – EN 429	2.0 mm
Total weight	ISO 23997 – EN 430	2800 g/m ²
Form of delivery	ISO 24341 – EN 426	Art. no. 21200_ _ _ 3 digit colour colour number
Sheet	Approx. 23 running metres x 200 cm (rolls)	
TECHNICAL PERFORMANCES	STANDARDS	iQ One
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B _{fl} s1 ≥ 8 kW/m ² Pass
Total VOC emissions	ISO 16000-6	≤ 100 µg/m ³ (after 28 days)
Chemical resistance	ISO 26987 – EN 423	Excellent
Slip resistance	DIN 51130 EN 13893 BS 7976-2	R9 ≥ 0.3 Low risk of slip
Wet room approval	EN 13553 Annex A GBR approval system	Watertight Certified
Residual indentation	ISO 24343-1 – EN 433	Required value: ≤ 0.10 mm Average measured value: 0.02 mm
Dimensional stability	EN 14565 Annex C	≤ 0.20 %
Castor chair test	ISO 4918 – EN 425	Suitable
Flexibility	ISO 24344 – EN 435	Pass
Underfloor heating		Suitable – max 27°C
Light fastness	EN ISO 105-B02	≥ level 6
Colours		38


The above information is subject to modification for the benefit of further improvement. (09/15).

CUSTOMS TARIFF : 482050000000F

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



Logistics Information



General Information



According to European Classification ISO 10874 - EN 685

