

## Technical Datasheet

# Acoustic comfort underlayer Tarkomfort Premium

UNDERLAY & OVERLAY SOLUTIONS

## DESCRIPTION

Loose-laid engineered underlayer, made of viscoelastic polymer with double sided anti-slip texture for enhanced acoustic performance.

### Key features:

- High-performance acoustic insulation: high-impact sound reduction (19 dB with iD Inspiration Click) and in-room noise reduction (72 dB).
- High-performance solution with good static indentation resistance (0.18mm with iD Inspiration Click).
- Thermal resistance standard respected: 0,02 m<sup>2</sup>/W
- Minimal thickness, ideally suited for renovation.
- Quick and easy to install: 1m roll to be handled and light weighted.
- Loose-lay for easy removal at end of life.
- Available in 15lm and 73lm rolls

### Subfloor type & applications:

- Residential and commercial applications.
- Screed, concrete surfaces, floorboards.
- Compatible with underfloor heating.

### Compatible flooring:

- iD Inspiration Click in planker tiles.

### Main segments of application:



## INSTALLATION

- Unroll and acclimatize in the room for at least 48 hours (> 18°).
- The subfloor must be dry and clean.
- Fully loose-laid on the substrate.
- Fully bonded with the floorcovering.
- Use a specific acrylic adhesive for gluing PVC over PVC\*. We recommend to downsize the spatula.
- Wait for 48h before laying floorcovering.

## TECHNICAL INFORMATION

### Product

Size (mm)	15 length x 1 width
Thickness (mm)	1.0
Total density (g/m <sup>2</sup> )	100 (1.5kg/roll)

### Packaging

Roll with chuck weight (kg)	1.6
Rolls per pallet	35
Pallet size (m)	1.2 length x 0.8 width x 1.19 height
Pallet weight (kg)	66
Min. order	1 roll (15m <sup>2</sup> )

## ARTICLE CODE

	SAP Code	EAN Code
Black 15 lm	24992030	3423128504569
Black 73lm	24992032	3423128560749

## CLEANING & MAINTENANCE

No cleaning or maintenance required.