

Technical Datasheet

Acoustic comfort underlayer Tarkomfort Pro

UNDERLAY & OVERLAY SOLUTIONS

DESCRIPTION

Loose-laid underlayer made of siliconised PET carrier film with high-resistance polyurethane layer and non-woven backing. Specially designed to tackle noise and for floating installation.

Key features:

- Powerful acoustic insulation, reducing both impact sound and in-room noise.
- Enhanced durability through its high-density, heavy-duty composition (1,500g per m²).
- Easy installation and removal with woven anti-slip surface gripping floorcovering and its loose-lay solution.
- Reduces impact sound by 13dB with iD Inspiration Click and Starfloor Click.
- Lowers in-room noise by 74dB with iD Inspiration Click and Starfloor Click.

Subfloor type & applications:

- Residential and commercial applications.
- Concrete subfloor.

Compatible flooring:

- LVT Click in planks or tiles.

Main segments of application:



INSTALLATION

- Unroll and acclimatize in the room for at least 24 hours (> 18°).
- The subfloor must be dry and clean.
- Loose-lay the underlayer on the substrate (tackifying side facing up to the LVT).
- Remove the protective film gradually.
- Lay the floorcovering, no glue needed.
- No waiting time before walking.

TECHNICAL INFORMATION


Product

Size (m)	10 length x 1 width
Thickness (mm)	1.5
Total density (g/m ²)	1500 (15kg/roll)

Packaging

Roll with chuck weight (kg)	17
Rolls per pallet	40
Pallet size (m)	1.02 length x 0.8 width x 1.02 height
Pallet weight (kg)	622.5
Min. order	1 roll (10m ²)

ARTICLE CODE

		SAP Code	EAN Code
	Grey	24992020	3423128460421

CLEANING & MAINTENANCE

No cleaning or maintenance required.

