Technical Datasheet

Acoustic comfort underlayer Tarkomfort Self-Adhesive*

UNDERLAY & OVERLAY SOLUTIONS

DESCRIPTION

Seld-adhesive underlayer made of mineral fillers and polyurethane binders to improve acoustic performance easily under glue-down LVT.

Key features:
- Reduces impact sound to 15 dB.
- High-class solution for reducing both impact sound and in-room noise.
- 90% natural raw materials, free from plasticizers and heavy metals.
- Resistance to high-traffic thanks to its high-density material.
- Can be use immediatly after installation.
- Stands up to static indentation: < 0.20mm.
- Time-saving and easy installation.

Subfloor type & applications:
- Residential and light commercial applications**.
- Concrete, existing hard floorings.

Compatible flooring:
- LVT Glue-down (planks or tiles)

Main segments of application:



INSTALLATION

- The subfloor must be dry and clean.
- Loose-lay the underlayer on the substrate.
- Remove its protective film gradually.
- Lay floorcovering, 90° to the underlayer. No glue needed thanks to its self-adhesive system.
- No waiting time before walking.

TECHNICAL INFORMATION

Product

Size (mm)	6.5 length x 1 width
Thickness (mm)	1.8
Total density (g/m²)	2,600 (16.9kg/roll)

Packaging

Rolls per pallet	40
Pallet size (m)	1.2 length x 0.8 width x 1.02 height
Pallet weight (kg)	698.5
Min. order	1 roll (6.5m²)

ARTICLE CODE

		SAP Code	EAN Code
	Black	24992040	3423128523669

CLEANING & MAINTENANCE

No cleaning or maintenance required.

* Under validation
** Check with your technical service

Tarkett