

# CEMENTI CLICK

## TECHNICAL DATA

Certification & classification	Standards	Cementi Click
Type of floor covering	EN 16511	Loose-laid panels-Semi-rigid multilayer modular floor (MMF) covering panels with wear resistant top layer
Classification	EN 16511	Commercial: 33
<b>Technical characteristics</b>		
Total thickness	ISO 24337	7,5 mm
Total weight	EN ISO 23997	12000 g/m <sup>2</sup>
Dimensions	ISO 24337	Planks: 1235 x 200 mm, 6 planks/box = 1,482 m <sup>2</sup> (44 boxes) Tiles: 920 x 460 mm, 4 tiles/box = 1,693 m <sup>2</sup> (40 boxes)
Surface treatment (PUR)		Yes
Beveled edges		Yes -Micro Bevel
<b>Technical performances</b>		
Dimensional stability	EN ISO 23999	≤ 0,10 %
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1 loose laid on concrete and on wood
Residual indentation	EN ISO 24343-1	≤ 0,2 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Impact sound reduction	EN ISO 717-2	19 dB
Light fastness	EN ISO 105-B02	≥ 6
Resistance to staining	EN 438-2	Groups 1 & 2: grade 5 Group 3: grade 4
Wear resistance	EN 13329 A method	AC5 (≥ 6000 cycles)
Impact resistance	EN 13329	IC3 (≥ 1600 mm)
Micro-scratch resistance	EN 16094	MSR-A2
Swelling	ISO 24336	≤ 18 %
Slip resistance	DIN 51130 EN 13893	R10 μ ≥ 0,30
Antistatic performance	EN 1815	< 2 kV > 10 <sup>9</sup> Ohm
Thermal resistance	EN 12667	≤ 0,05 m <sup>2</sup> K/W
Underfloor heating	-	Suitable
TVOC emissions after 28 days	EN 16516	≤ 10 μg/m <sup>3</sup> *

\* Platinum TIAQ.

The above information is subject to modification for the benefit of further improvement. (06/17).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for these instructions. CE Marking : according to the European Regulation N° 305/2011, the Declaration of Performance n° 0132-0069-DoP-2017-11 is available on our website [www.tarkett.com](http://www.tarkett.com)

CUSTOMS TARIFF : 4820 5000 00



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



European classification  
EN ISO 10874



[www.blauer-engel.de/uz120](http://www.blauer-engel.de/uz120)