

## Technical Datasheet

# Cold welding type A for PVC in sheets

ADHESIVES & WELDING

## DESCRIPTION

Cold welding solution in a tube with a needle.

Specially designed for heterogeneous vinyl floorcovering sheets that have been overlapped and double cut.

### Key features:

- Invisible joint.
- Easy to apply with the needle that acts as a guide.
- Quick-drying solution.

### Compatible flooring:

- Heterogeneous vinyl floorings in rolls.

### Main segments of application:



## TECHNICAL INFORMATION

### Product

Unit weight (g) 44 (20lm)


### Packaging

Pieces per box	24 tubes
Box size (cm)	310 x 220 x 100
Box weight (kg)	1.056
Min. order	1 box

## INSTALLATION

- The sheets must be overlapped and double-cut.
- Fix the tape over the joint and use hand roller to ensure bonding.
- Cut tape along the seam (rolling knife recommended).
- Insert the needle of the tube into the joint and press regularly. Make sure you apply enough liquid along the joint.
- Take the tape away (after approximately 10 min).
- DO NOT remove any excess of liquid, it will disappear during normal wear.
- Cold liquid welding can be carried out 24 hours after the installation of the vinyl floor covering.
- Cold welding not valid for homogeneous, LVT and linoleum floorings, and tiles format.

## ARTICLE CODE

	SAP Code	EAN Code
 Transparent Cold Welding	1490 002	3423128423433

## CLEANING & MAINTENANCE

No cleaning or maintenance required.