


DESSO Textile floor covering - Broadloom

Desso &Ex

Preliminary specification according to EN 1307



| | | | | | | | | |
|-------------------------------------|------------------|------------------------------|-------|--------------------|--------|------|------|------|
| Type of manufacture | ISO 2424 | Tufted 1/10 " | | | | | | |
| Aspect | ISO 2424 | Cut pile | | | | | | |
| Dye method | | Print | | | | | | |
| Width | cm | 400 | ft | 13.1 | | | | |
| Primary backing | ISO 2424 | Polyester - polyamide fleece | | | | | | |
| Secondary backing | ISO 2424 | Polypropylene woven | | | | | | |
| Pile fibre composition | ISO 2424 | BCF Polyamide 6 | | | | | | |
| Total thickness | ISO 1765 | mm | 6.5 | inch | 0.3 | | | |
| Effective pile thickness | ISO 1766 | mm | 4.3 | inch | 0.17 | | | |
| Total mass | ISO 8543 | g/m ² | 1930 | oz/yd ² | 57.0 | | | |
| Total pile mass | ISO 2424 | g/m ² | 980 | oz/yd ² | 28.9 | | | |
| Effective pile mass | ISO 8543 | g/m ² | 590 | oz/yd ² | 17.4 | | | |
| Pile density | ISO 8543 | g/cm ³ | 0.137 | lb/in ³ | 0.0050 | | | |
| Number of tufts | ISO 1763 | /dm ² | 1735 | /yd ² | 145063 | | | |
| Stroll test | ISO 6356 | kV | ≤ 2,0 | | | | | |
| Vertical resistance | ISO 10965 | Ohm | - | | | | | |
| Horizontal resistance | ISO 10965 | Ohm | - | | | | | |
| Use classification | EN 1307 | 33 Commercial - heavy use | | | | | | |
| Luxury rating | EN 1307 | LC 2 | | | | | | |
| Impact sound reduction ΔL_w | ISO 10140 | dB | 25 | | | | | |
| Sound absorption | ISO 354 | Freq. Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| | | α_s | 0.00 | 0.05 | 0.10 | 0.20 | 0.40 | 0.55 |
| Noise reduction | ISO 354 | α_w | 0.20 | | | | | |
| Thermal resistance | ISO 8302 | m ² .K/W | 0.084 | | | | | |
| Flammability | EN 13501-1 | Cfl - s1 (glued tested) | | | | | | |
| Prodis - GUT | www.pro-dis.info | CD6A9D5D | | | | | | |


Manufactured by:

EN 14041
Tarkett BV

1658-CPR-3146
Taxandriaweg 15

NL - 5142 PA Waalwijk

Use classification may vary with specific colours and/or designs



DESSO flooring products are to be installed in full accordance with Tarkett's installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20221015