HERITAGE

WOOD - PRODUCT DATASHEET 2024



TECHNICAL DATA (EN 13489)		14 mm			
Reaction to fire	EN 14342 Table 1	Dfl-s1			
Emission of formaldehyde	EN 14342	E1			
Brinell hardness (average value) Oak	(BHN) EN1534	3,7			
Reduction of sound weighted index ΔL _W in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥17			
Thermal insulation value (RT m² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141			
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,11			
Construction: softwood veneer and lamella	3-layer				

INSTALLATION						
Installation method	2-lock for floating or glue down					
Installation instruction	Download from www.tarkett.com Contact your supplier for more details					
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating underfloor heating system						
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²						

RECOMMENDED ACCESSORIES					
Installation	Tarkofoam II / Tarkoflex II Installation kit				
Aesthetics	Skirting Transition moulding Pipe covers				
Care & Maintenance	Tarkoclean for hardwax oiled floors Refresher for hardwax oiled floors				
See more alternatives and the complete range of accessories @ www.tarkett.com					

MAINTENANCE

These Tarkett wooden floors have a Proteco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details. Please always refer to maintenance guidance available on websites.

See maintenance instructions @ www.tarkett.com



















HERITAGE

WOOD - PRODUCT DATASHEET 2024

DESIGN

Wooden floors with an extra rustic look have all the genuine features of the wood and are proudly featured. Both the cracks and the knots are emphasized through the application of hardwax oils to the deep brushed surfaces. Skillfully handcrafted minibevels enhance the exclusive format of the planks.

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side, handmade)	Character	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Heritage Oak Old White	7876128	2 000 x 162 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	1,94	69,84	7,9
Heritage Oak Lime Stone	41007002	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	2,51	87,85	7,9
Heritage Oak Urban Grey	41007007	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	2,51	87,85	7,9
Heritage Oak Blonde	41007013	2 000 x 190 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	2,28	79,80	7,9
Heritage Oak	41007001	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	2,51	87,85	7,9
	41007009	2 000 x 190 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	2,28	79,80	7,9
Heritage Oak Old Grey	41007005	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	2,51	87,85	7,9
Heritage Oak Old Brown	41007004	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Deep brushed	Minibevel	Expressive	1	0190-0105	3,5	6	2,51	87,85	7,9
Due to the nature of the material this table shows typical values.														

and to the natare of the material this table show

1: Quercus Robur & Quercus Petraea



Heritage Oak Old White



Heritage Oak Lime Stone



Heritage Oak Urban Grey



Heritage Oak Blonde



Heritage Oak



Heritage Oak Old Grey



Heritage Oak Old Brown

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com

