

# PLAY

## WOOD - PRODUCT DATASHEET 2021



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1 (when applicable / EN 13501)	Dfl-s1*
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Ash Oak	(BHN) EN1534	4,0 3,7
Taber Abraser/Lacquer's wear resistance Protoco Natura <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	N/A
Reduction of sound weighted index $\Delta L_w$ in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	$\geq 17$
Thermal insulation value (RT m <sup>2</sup> K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K) 13 mm 14 mm	EN 12664 / EN 14342:2013	0,104 0,11
Construction	3-layer with softwood core	

\* CfI-s1 for lacquered products can be provided on demand.

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from <a href="http://www.tarkett.com">www.tarkett.com</a> Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m <sup>2</sup>	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting, Transition moulding, Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ <a href="http://www.tarkett.com">www.tarkett.com</a>	

MAINTENANCE
These Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ <a href="http://www.tarkett.com">www.tarkett.com</a>

Play 14 mm Protoco Natura      Play 13 mm Protoco Natura



2-LOCK



# PLAY

## WOOD - PRODUCT DATASHEET 2021

### DESIGN

A collection of floors that highlights the quality of the wood through new and experimental effects on its surface, giving every board a touch of the extraordinary.

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Character	Colour	Latin name	DoP no.	Wear layer thk (mm)	Board/pack	m2/pack	m2/pallet	Net weight/m2 (kg)
Play Ash Ivory Plank	41006008	2 000 x 162 x 13	1-strip	Proteco Natura	-	Minibevel	Calm	White	1	0190-0103	2,5	6	1,94	69,84	7,3
Play Oak Winter Plank	7876007	2 000 x 162 x 14	1-strip	Proteco Natura	Brushed	Handmade bevel	Expressive	White	2	0190-0105	3,5	6	1,94	69,84	7,9
	7876024	2 520 x 162 x 14	1-strip	Proteco Natura	Brushed	Handmade bevel	Expressive	White	2	0190-0105	3,5	6	2,45	88,20	7,9
Play Oak Marble Plank	7876009	2 200 x 162 x 14	1-strip	Proteco Natura	Brushed	Minibevel	Expressive	Warm grey	3	0190-0105	3,5	6	2,14	77,04	7,9
Play Oak Charcoal Plank	7876106	2 000 x 162 x 14	1-strip	Proteco Natura	Brushed	Minibevel	Calm	Black	3	0190-0105	3,5	6	1,94	69,84	7,9

Due to the nature of the material this table shows typical values.

1: Fraxinus Angustifolia, 2: Quercus Alba, 3: Quercus Robur & Quercus Petraea



Play Ash Ivory Plank



Play Oak Winter Plank



Play Oak Marble Plank



Play Oak Charcoal Plank

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or [www.tarkett.com](http://www.tarkett.com).

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit [www.tarkett.com](http://www.tarkett.com)