

STARFLOOR CLICK 55 & 55^{PLUS}

TECHNICAL DATA

TECHNICAL DATA	STANDARD	STARFLOOR CLICK 55
CLASSIFICATION		
Classification	EN ISO 10582 EN ISO 10874	Heterogeneous Compact Resilient Floorcovering Residential: 23 - Commercial: 33
Wear layer binder content	EN ISO 10582	Type I
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346	4.5 mm
Total weight	EN ISO 23997	8 kg/m ²
Wear layer thickness	EN ISO 24340	0.55 mm
Locking system		Click
Bevelled edges		Yes
Surface treatment (PUR)		Extreme®
Form of delivery	EN ISO 24342 Planks EN ISO 24342 Tiles	19.05 x 121.1 cm = 7 planks/box = 1.61 m ² /box 24.05 x 149.1 cm = 5 planks/box = 1.79 m ² /box 32.38 x 60.1 cm = 9 tiles/box = 1.75 m ² /box
PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)		
Declaration of Performance	EN 14041	0197-0010-DoP-2016-04
Reaction to fire	EN 13501-1	B _n -s1 loose laid on concrete
Electrostatic properties	EN 1815	≤ 2 kV on concrete
Thermal resistance	EN ISO 10456	0.04 m ² K/W
Slip resistance	EN 13893	μ ≥ 0.3
TECHNICAL PERFORMANCES		
Dimensional stability	EN ISO 23999	≤ 0.10%
Impact sound reduction	NF EN ISO 717 / 2	ΔL _w 3 dB
Slip resistance	DIN 51130	R9 / R10 depending on embossing
Locking strength [kN/m]	EN 10582	≥ 2 kN/m
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Light fastness	EN ISO 105-B02 (method 3 ^a)	≥ 6
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Chemical resistance	EN ISO 26987	Very good
Underfloor heating		Suitable – max. 27°C
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
ENVIRONMENTAL PERFORMANCES		
Total VOC emissions	ISO 16000-9	≤ 10 µg/m ³ (after 28 days)
COLOURS		

28

The above information is subject to modification for the benefit of further improvement. (10/18).

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



Customs Tariff: 4820 5000