

STARFLOOR

Technical data sheet
08-2016



TYPE	UNIT	FEATURE
Type of floor covering		Heterogeneous Compact Resilient Floorcovering
Material group		5925 / 5926* / 5927**
Dimensions	cm	15,2 x 91,4 / 45,7x45,7* / 30,5x61**
Locking system	Type	Self-adhesive
Classification	EN ISO 10874	Domestic: 22
Commercial warranty	Years	10 years residential use

FEATURE	NORM	TARKETT TYPICAL VALUE
Technical characteristics		
Total thickness	EN ISO 24346	2,00 mm
Wear layer thickness	EN ISO 24340	0,20 mm
Wear layer binder content	ISO 10582	Type I
Dimension - Length	EN ISO 24342	15,2 / 45,7* / 30,5**
Dimension - Width	EN ISO 24342	91,4 / 45,7* / 61**
Surface Treatment (PUR)		Yes - Extreme®
Bevelled edges		No
Technical performances		
Dimensional stability	EN ISO 23999	≤ 0,25 %
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Reaction to fire	EN 13501-1	B _{fl} -s1 loose laid on concrete and on wood
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Impact sound reduction	EN ISO 717-2	ΔL _w = 2 dB
Thermal resistance	EN ISO 10456	0,02 m ² K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Chemical resistance	EN ISO 26987	Slightly affected (1)
Slip resistance	DIN 51130 / EN 13893	R9 / μ ≥ 0,30
Electrical properties	EN 1815 / EN 1081	<2 kV on concrete / > 10 ⁹ Ohm
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Underfloor heating		Suitable - max. 27 °C
Environment		
TVOC 28 days AgBB test		≤ 100μg/m ³
Recycled content		0%
Recyclable		100%
Plasticizer		Phthalate-free technology

LOGISTICS INFORMATION

15 planks/box 10* / 11** tiles/box	2,08 / 2,08* / 2,04** m ² /box	3,59 kg/m ² planks 3,87 kg/m ² tiles */**	120 / 104* / 104** boxes/palette	249,6 / 216,32* / 212,16** m ² /palette
---------------------------------------	--	--	-------------------------------------	---

EN 14041

Starfloor SA

CE EN 14041:2004

0131-0037-DeP-2013-07
<http://www.home.tarkett.com>

Distributed by: Tarkett GDL SA
2 Op der Sang
L - 9779 Lentzweiler

TARKETT
BALANCED
CHOICE

100 %
Recyclable

Better Indoor
Air Quality
*TVOC AT 28 DAYS

PHTHALATE
FREE
Technology
* EXCEPT RECYCLED CONTENT

TARKETT
Extreme
Protection

GUARANTEE
10
Residential
Use

Easy to clean

FAST



THE ULTIMATE
FLOORING EXPERIENCE