








Starfloor Click 30^{PLUS}

		EN ISO 10582
		EN ISO 10874 23  31 
		36002
	ISO 24342	122 x 18.3 cm = 9
		15
	EN ISO 24346	4,00 mm
	EN ISO 24340	0,30 mm
	ISO 10582	
	EN ISO 24342	122 cm
	EN ISO 24342	18.3 cm
	ISO 29997-EN430	7,4 kg/m ²
	EN ISO 23999	≤ 0,10 %
	EN ISO 23999	≤ 2 mm
	EN 13501-1	
	EN ISO 24343-1	≤ 0,08 mm
	EN 424	
	ISO 4918 - EN 425	
	EN ISO 717-2	ΔLw = 3 dB
	EN ISO 10456	0,03 m ² K/W
	EN ISO 105-B02 (method 3a)	≥ 6
	EN ISO 26987	
	DIN 51130 / EN 13893	R9 / R10
	EN 1815 / EN 1081	<2 kV
	EN ISO 24345	≥ 50N / 50mm
		≤ 100µg/m ³
		100%



EN ISO 10582
Starfloor Click 30

Starfloor Click 30^{PLUS}
 No. 0131-0035-DoP-2013-07
<http://www.home.tarkett.com>
 Distributed by: Tarkett GDL SA
 2 Op der Sang
 L - 9779 Lentzweiler
 EN 14041:2004

TARKETT
BALANCED
CHOICE

100 %
Recyclable

< 100µg/m³
Better Indoor
Air Quality
*TVOC AT 28 DAYS

PHTHALATE
FREE
Technology

TARKETT
Extreme
Protection

GUARANTEE
15
Residential