

iD INSPIRATION 40

TECHNICAL DATA


CERTIFICATION & CLASSIFICATION	STANDARDS	iD Inspiration 40
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering
Classification	EN ISO 10874	Domestic: 23 Commercial: 32 Industrial: 41
TECHNICAL CHARACTERISTICS	STANDARDS	iD Inspiration 40
Total thickness	EN ISO 24346	2,2 mm
Wear layer thickness	EN ISO 24340	0,4
Total weight	EN ISO 23997	3700 g/m ²
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342	Planks 16,66 x 100 cm, 25 planks/box = 4,17 m ² 20 x 122 cm, 17 planks/box = 4,15 m ² Tiles 50 x 50 cm, 17 tiles/box = 4,25 m ² 50 x 100 cm, 8 tiles/box = 4,00 m ²
Surface treatment (PUR)		Yes - TopCleanXP™
Beveled edges		No
TECHNICAL PERFORMANCES	STANDARDS	iD Inspiration 40
Dimensional stability	EN ISO 23999	≤ 0,10 %
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Reaction to fire	EN 13501-1	B _{fl} -s1 glued over concrete substrate B _{fl} -s1 glued over wood substrate
Residual indentation	EN ISO 24343-1	≤ 0,05 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Impact sound reduction	EN ISO 717-2	ΔL _w = 3 dB
Reduction of in-room impact noise	EN ISO 31-074	Class C (L _{n,e,w} < 85 dB)
Thermal resistance	EN ISO 10456	0,02 m ² K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Chemical resistance	EN ISO 26987	Not affected (0)
Slip resistance	DIN 51130 EN 13893	R9 / R10 depending on embossing μ ≥ 0,30
Electrical properties	EN 1815 EN 1081	<2 kV on concrete > 10 ⁹ Ohm
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Underfloor heating		Suitable - max. 27 °C

The above information is subject to modification for the benefit of further improvement. (07/16).
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.
Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF : 482050000000F



Logistics Information



Surface treatment



General Information



According to European Classification ISO 10874 - EN 685

