

iD MIXONOMI

TECHNICAL DATA

Certification & classification	Standards	iD Mixonomi
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering
Classification	EN ISO 10874	Domestic: 23 Commercial: 34 Industrial: 43
Technical characteristics		
Total thickness	EN ISO 24346	2.5 mm
Wear layer thickness	EN ISO 24340	0.7 mm
Total weight	EN ISO 23997	3950 g/m ²
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342	Diamond Small 19.243 x 33.329 cm, 80 units/box = 2.56 m ² Diamond Large 38.486 x 66.66 cm, 20 units/box = 2.56 m ² Herringbone Left 8.33 x 38.486 cm, 80 units/box = 2.56 m ² Herringbone Right 8.33 x 38.486 cm, 80 units/box = 2.56 m ² Hexagon Small 20 x 23.094 cm, 60 units/box = 2.04 m ² Hexagon Large 33.33 x 38.486 cm, 20 units/box = 1.92 m ² Rectangle 10 x 50 cm, 75 units/box = 3.75 m ² Square 25 x 25 cm, 60 units/box = 3.75 m ² Trapeze 16.66 x 38.486 cm, 40 units/box = 1.92 m ² Triangle Small 19.243 x 19.243 cm, 120 units/box = 1.92 m ² Triangle Large 38.486 x 38.486 cm, 40 units/box = 2.56 m ²
Surface treatment (PUR)		Yes - TopCleanXP™
Beveled edges		No
Technical performances		
Dimensional stability	EN ISO 23999	≤ 0.10 %
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Reaction to fire	EN 13501-1	B _{fl} -s1 glued over concrete substrate B _{fl} -s1 glued over wood substrate
Residual indentation	EN ISO 24343-1	≤ 0.05 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Impact sound reduction	EN ISO 717-2	ΔL _w = 2 dB
Reduction of in-room impact noise	EN ISO 31-074	Class C (L _{n,e,w} < 85 dB)
Thermal resistance	EN ISO 10456	0,02 m ² K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Chemical resistance	EN ISO 26987	Very good
Slip resistance	DIN 51130 EN 13893	R10 μ ≥ 0.30
Electrical properties	EN 1815 EN 1081	<2 kV on concrete > 10 ⁹ Ohm
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Underfloor heating		Suitable - max. 27 °C
Environmental tag		
VOC emission	ISO 16000-9	≤ 10μg/m ³
Recycled content	-	32%
Recyclable	-	100%
Plasticizer	-	Phtalate-free

The above information is subject to modification for the benefit of further improvement. (11/18).
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.
Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF : 4820 5000 00

