

TS 30 / TS MAX 30 / TS 55

iD Generation 30 & 55

TECHNICAL DATA	Standards	TS 30	TS MAX 30	TS 55	iD New Gen 30	iD Pro Gen 55
CLASSIFICATION	EN ISO 10582	Heterogeneous PVC floor covering				
	EN ISO 10874	Domestic: 23	Domestic: 23	Domestic: 23	Domestic: 23	Domestic: 23
		Commercial: 31	Commercial: 31	Commercial: 33	Commercial: 31	Commercial: 33
TECHNICAL CHARACTERISTICS						
Total thickness	EN ISO 24346	2.00 mm	3.00 mm	5.00 mm	4+1mm IXPE backing	5+1mm IXPE backing
Total weight		3560g/m²	5630g/m²	9030g/m²	8310g/m²	10200g/m²
Bevelled edges		NO			Microbevels	
Surface treatment		PU treatment				
Form of delivery	EN ISO 24342	Plank 184 x 1219.2 mm	Plank 184 x 1219.2 mm	Plank 184 x 1219.2 mm	Plank 178.1 x 1219.2 mm	Plank 178.1 x 1219.2 mm
		15 planks / box (3.37m²)	10 planks / box (2.25m²)	9 planks / box (2.02m²)	8 planks / box (1.74m²)	8 planks / box (1.74m²)
		90 boxes/pallet (303.30m²)	90 boxes/pallet (202.50m²)	70 boxes/pallet (141.40m²)	50 boxes/pallet (87.00m²)	50 boxes/pallet (87.00m²)
		Tile 500 x 500 mm	Tile 500 x 500 mm	Tile 500 x 500 mm	Tile 607.2 x 303.1 mm	Tile 607.2 x 303.1 mm
		14 tiles / box (3.50m²)	9 tiles / box (2.25m²)	6 tiles / box (1.50m²)	8 tiles / box (1.47m²)	7 tiles / box (1.29m²)
		60 boxes/pallet (210.00m²)	60 boxes/pallet (135.00m²)	72 boxes/pallet (108.00m²)	66 boxes/pallet (97.02m²)	66 boxes/pallet (85.14m²)
TECHNICAL PERFORMANCE						
Reaction to fire	EN 13501-1	Bfl-s1				
Slip resistance	DIN 51130	R9				
Residual Indentation	EN ISO 24343-1	≤ 0.20 mm				
Impact sound reduction	NF EN ISO 717/2	△LW = 1dB	△LW = 2dB	△LW = 13dB	△LW = 17dB	△LW = 19dB
Castor chair	ISO 4918 (EN 425)	No damage				
Furniture leg	EN 424	No damage				
Curl resultant to heat 6h at 80 °C (mm)	EN ISO 23999	≤ 2.00 mm				
Light fastness	EN ISO 105-B02	≥ 6				
Dimensional stability	EN ISO 23999	≤ 0.25 %				
Resistance to chemicals	EN ISO 26987 (EN 423)	Good resistance				
VOC emission	ISO 16000-9	≤ 100 µg/m³ (28 days)				
Recyclable	-	100%				
Plasticizer	-	Phthalate-free				
Commercial warranty	-	10 years				
Colours	-	Wood: 30 / Stones: 26 / Texture: 24				

The above information is subject to modification for the benefit of further improvement (04/2025).

For the latest information, please visit our website: www.Tarkett-Asia.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

