Wallgard

FISA TEHNICA

Clasificare	Normativ	Caracteristici tehnice
Tip de pardoseala	EN 259-1	Tapet omogen, din vinil
Caracteristici tehnice	**Normativ**	**Caracteristici tehnice**
Grosime totala	EN ISO 24346	1,30 mm
Greutate totala	EN ISO 23997	2100 g/m²
Grosimea stratului de uzura	EN ISO 24340	1,30 mm
Tratament de suprafata		PU SHIELD
Performante tehnice	**Normativ**	**Caracteristici tehnice**
Declaratia de performanta	EN 15102	0019-0043-DoP-2013-07
Reactia la foc	EN 13501-1	B-s2,d0
Performante tehnice	**Normativ**	**Caracteristici tehnice**
Rezistenta culorii la lumina artificiala	ISO 105-B02	≥ 7
Certificare wetroom	GBR class VT	DA
Stabilitate dimensionala	EN ISO 23999	≤ 0.4%
Rezistenta la chimicale	ISO 26987	Excelenta
Rezistenta la bacterii	ISO 846 Part C	Nu favorizeaza dezvoltarea bacteriilor
Certificare Clean room	ISO 14644-1	ISO clasa 4
Performante sustenabile	**Normativ**	**Caracteristici tehnice**
Reciclare prin programul ReStart®		Da, este reciclabil
Continut reciclabil		25,5 %
Total emisii VOC	EN 16516	Platinum (≤ 10 µg/m³)
Emisii formaldehide		E1
Dimensiuni si design		
Dimensiune rola		Rola de 2 x 30 m
Design-uri disponibil		13

The above information is subject to modification for the benefit of further improvement (09/12/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.