

# Linoleum xf<sup>2</sup>



Certification & Classification	Standards	Veneto xf <sup>2</sup> 2,5 mm
Type of flooring	ISO 24011/EN 548	Linoleum
CE classification	EN 14041	yes
Classification UPEC		U4P3E1/2C2
Classification	ISO 10874-EN685	
	Domestic	23
	Commercial	34
	Light industrial	43
TECHNICAL CHARACTERISTICS	Standards	
Surface treatment		xf <sup>2</sup>
Total thickness	ISO 24346-EN428	2,5 mm
Total weight	ISO 23997-EN430	ca.3000 g/m <sup>2</sup>
Residual indentation	ISO 24343-1-EN433	ca.0.08mm
Flexibility	ISO 24344-EN435 Method A	≤ 30mm Ø
Form of delivery	ISO 24341-EN426	Rolls : ≤ 30 m * 2 m
TECHNICAL PERFORMANCE		
Fire classification	EN 13501-1	C <sub>fl</sub> -s1
Impact sound reduction	ISO 140-8 / EN ISO 717-2	≤ 6dB
Impact sound reduction with Elafono	ISO 140-8 - EN ISO 717-2	14dB
Castor chair	ISO 4918-EN425	Suitable for office chairs with castor type W (Norm EN 12529)
Static electrical propensity	EN 1815	< 2kV
Slip resistance	EN 13893	DS≥0.30
Dynamic coefficient of friction	DIN 51130	R9
Chemical resistance	ISO 26987-EN423	Resistant to dilute acids, oils, fats and current solvents and alkalis.
Thermal resistance	ISO 10456 / EN 12524	0.015m <sup>2</sup> K/W
Underfloor heating		Suitable
Light fastness	ISO 105-B02, Method 3	≥ 6
Determination of the antibacterial activity	ISO 22196	yes, naturally
Colours		72