

# Omnisports SPEED



## KEY POINTS

### Description :

Vinyl sports floor covering over fibreglass with PVC foam backing. Protected with Top Clean XP® (dirt-resistant treatment for ease of maintenance)

### Type of installation :

- Glued Installation

### Surface Texture :

Sorrent

### Compatible Installation :

Association possible with a sub construction (Lumaflex type)

### Installation instructions and maintenance guide :

On request

### Dimensions (EN 426/EN 427) :



2 m



20.5 lm or 23 lm

### Total thickness (EN 428) :



3.45 mm (± 0,15mm)

### Total weight (EN 430) :



3.295kg/m<sup>2</sup> (± 500g)

Technical data in force as from the date of publication (05/2013). The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement.

For more detailed technical information, please contact Tarkett.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.

Properties	Standard	Omnisports SPEED
<b>Vinyl Indoor sports flooring with elastic point area deformation</b>		
<b>must be installed on a sub-construction to reach the requirements of the EN 14 904 standard</b>		
<b>Sports properties</b>		
Friction	EN 13036-4	95
Shock Absorption %	EN 14 808	6
Vertical deformation	EN 14 809	0,4
Vertical ball rebound	EN 12235	98%

Classification		
Reaction to fire	EN 13501-1	Cfl-S1 Glued installation
Hygiene	-	Does not contribute to infection spreading

Technical characteristics		
Wear Layer	EN 429	0.65 mm
Resistance to wear	EN ISO 5470-1	0.124 g
Resistance to indentation	EN 1516	0.18mm
Behaviour under a rolling load	EN 1569	-
Resistance to impacts	EN 1517	No degradation

Specific characteristics		
Surface treatment	Topclean X-treme performance protection	
Maintenance		With Dynatech Trophy

**COMPATIBLE SLABS:** Concrete, asphalt screed, anhydrite screed. Any deviation of the slab must be corrected prior installation (6 mm under a 3 m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards.

## Omnisports Speed



52%

Natural

100%

26%

Recyclable Recycled content



\*TVOC AT 28 DAYS



	EN 14041:2004	Manufactured by: Tarkett France 08200 Sedan FRANCE
	 	EN 14041 Omnisports Speed/Training

