

Omnisports Compact



KEY POINTS

Description :

Vinyl floor covering over fibreglass. Protected with Top Clean XP® (dirt-resistant treatment for ease of maintenance).

Type of Installation :

- Glued Installation over a Lumaflex sub construction or over the traditional support


Top Embossing :

Sorrent

Installation and maintenance guides :

On request

Dimensions (EN 426/EN 427) :



2 m


23 ml

Total Thickness (EN 428) :



2 mm (± 0,15mm)

Total Weight (EN 430) :



3,1 kg/m² (±200g)

Technical data in force as from the date of publication (05/2013).

The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement. For more detailed technical information, please contact Tarkett. Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.

Properties	Standard	Omnisports Compact
------------	----------	--------------------

Must be installed on a wooden sub construction like Lumaflex to reach the requirements of the EN14 904 standard

Properties		
Friction	EN 13036-4	101
Sock Absorption %	EN 14 808	not measured
Vertical deformation	EN 14 809	not measured
Vertical ball rebound	EN 12235	not measured

Classification		
Reaction to Fire	EN 13501-1	Bfl-S1 Glued installation
Hygiene	-	Does not contribute to infection spreading

Technical characteristics		
Wear Layer	EN 429	0,80
Resistance to wear	EN ISO 5470-1	not measured
Indentation	EN 1516	not measured
Behaviour under a rolling load	EN 1569	not measured
Resistance to impact	EN 1517	not measured

Specific Characteristics		
Surface treatment	Topclean X-Treme performance protection	
Maintenance		

COMPATIBLE SLABS: Concrete, asphalt screed, anhydrite screed. Any deviation of the slab must be corrected prior installation (6 mm under a 3 m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards.

Omnisports Compact



52%

Natural



100%
31%

Recyclable
Recycled content



<100 µg/m³
Better Indoor Air Quality
*TVOC AT 28 DAYS



ISO 14001
ENVIRONMENTAL MANAGEMENT SYSTEM

Tarkett

ISO 9001
QUALITY SYSTEM



EN 14041:2004
Bfl-S1
101

Manufactured by:
Tarkett France
08200 Sedan
FRANCE
EN 14081
Omnisports Compact