

**PRODUCT  
DATA SHEET**

# AQUARELLE DESIGN FLOOR 3m

TopClean PUR-reinforced

**Type of flooring**

**EN 649**

**Vinyl Floorcovering**

**Class of use**

**EN 685**



**23**



**32**



**41**

**Class**



**EN 428**

Total thickness

**2,00 mm**



**EN 429**

Wear layer thickness

**0,40 mm**



**EN 426**

Dimension

**15 - 25 m  
3m**



**EN 430**

Total weight

**2,150 kg/m<sup>2</sup>**



**EN 660-2**

Abrasion group

**T**



**EN 433**

Static  
indentation

**≤ 0,10 mm**

## Other Characteristics



**ISO 105/B02**

Light fastness

**≥ 6**



**EN 13501-1**

Fire Classification

**Bfl-s1**



**EN 12524**

Thermal resistance

**0,02 m<sup>2</sup>/kW**

for underfloor heating



**EN 13893**

**DIN 51130**

Slip resistance

**≥ 0,30 μ  
R9**



**EN 1815**

Static electrical  
propensity

**≤ 2 kV**



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.