

**PRODUCT
DATA SHEET**

AQUARELLE FLOOR 2 m

TopClean PUR-reinforced

Type of flooring

EN 649

Vinyl Floorcovering

Class of use

EN 685



23



31

Class



EN 428

Total thickness **1,500 mm**



EN 429

Wear layer thickness: **0,35 mm**



EN 426

Dimension **18- 25 m**
2m



EN 430

Total weight **2 400 kg/m²**



EN 660-2

Abrasion group **T**



EN 433

Static indentation **≤ 0,10 mm**

Static indentation

Other Characteristics



ISO 105/B02

Light fastness **≥ 6**



EN 12524

Thermal resistance **0,02 m²/kW**
for underfloor heating



Slip resistance

EN 13893 **≥ 0,30 μ**
DIN 51130 **R9**



EN 1815

Static electrical propensity **≤ 2 kV**



EN 13501-1

Fire Classification **Bfl-s1**



Aquarelle Floor 3m

0131-0005-DoP-2013-07
www.tarkett.se

Made by: Tarkett GDLSA,
Lentzweiler - LUXEMBURG



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.