

## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Heterogeneous commercial flooring designed for commercial interiors with heavy traffic. Glass fiber reinforced for stability and a polyurethane reinforced finish makes this product durable and easy to maintain.

### 1.2. Recommended areas for use:

- Education – Classrooms, corridors, multipurpose rooms, laboratories, cafeterias
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Healthcare – Patient rooms, exam rooms, lobbies, corridors, emergency rooms, critical care, laboratories
- Hospitality – Corridors, vending areas, lobbies, bathrooms

### 1.3. Manufacturer:

Tarkett North America      Phone (800) 899-8916  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkett.com](http://www.tarkett.com)  
E-mail: [info@tarkett.com](mailto:info@tarkett.com)

### 1.4. Proprietary Product Description:

1.4.1. **Construction:** Tarkett's Acczent has a PUR reinforced wearlayer composed of 90% binder content to minimize maintenance.

### 1.4.2. Styles:

- Product:
  - ACW-R (Acczent Wood)
  - ACF-R (Acczent Flourish)
  - ACC-R (Acczent Concrete)
  - ACT-R (Acczent Tisse)
  - ACZ-R (Acczent Zen)
- Thickness: 0.080" (2.0 mm)
- Wear layer thickness: 32 mil (0.8mm)
- Packaging: Available in 6' 6" (2 m) wide and approximately 76' linear feet (23 m) per roll

## 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Sheet material** meets ASTM F 1303, Type I, Grade 1, Class B performance sheet vinyl floorcovering with backing
- 2.2. **Heat Stability by Color Change** (ASTM F 1514):  $\Delta E \leq 8$
- 2.3. **Light Stability by Color Change** (ASTM F 1515):  $\Delta E \leq 8$
- 2.4. **Flexibility** (ASTM F 137): Passes
- 2.5. **Chemical Resistance** (ASTM F925): Passes
- 2.6. **Static coefficient of friction** (ASTM D 2047):  $\geq 0.5$  SCOF
- 2.7. **Static Load Limit** (ASTM F 970): Passes 175 psi  $\leq 0.005''$
- 2.8. **Flammability** (ASTM E648): Class 1 ( $\geq 0.45$  W/cm<sup>2</sup>)
- 2.9. **Smoke Development** (ASTM E 662):  $< 450$

## 3. INSTALLATION

3.1. See Heterogeneous Sheet flooring installation instructions for complete details.

### 3.2. Adhesives:

- **Tarkett 925 Adhesive:**  
Approximate Coverage:  
Porous Substrate: 250-300 sq. ft./gal.  
Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive:**  
Approximate Coverage:  
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett RollSmart Adhesive:**  
Approximate Coverage:  
Porous & Non-porous Substrate: 350 - 400 sq. ft. per gallon  
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett Cold Weld Liquid:**  
Approximate Coverage: 175 – 200 lin. ft. per 4.5 oz. tube

## 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

## 5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Acczent Maintenance Instructions for complete maintenance details.

### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)



**6. TECHNICAL SERVICES**

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)

Contact Technical Support at (800) 899-8916 or E-mail:

[Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

**7. LIMITED WARRANTY**

Limited 10 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

---

**Tarkett North America**

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916

[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)