



Acczent™ & Acczent Flourish™

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Heterogeneous commercial flooring designed for commercial interiors with heavy traffic. Glass fiber reinforced for stability and a polyurethane reinforced finish makes this product durable and easy to maintain.
- 1.2. **Manufacturer:**

Tarkett North America Phone (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com
E-mail: info@tarkett.com
- 1.3. **Proprietary Product Description:**
 - **Construction:** Tarkett's Acczent has a PUR reinforced wear layer composed of 90% binder content to minimize maintenance.
 - **Styles:**
 - Products:
 - ACW-R (Acczent Wood)
 - ACF-R (Acczent Flourish)
 - ACC-R (Acczent Concrete)
 - ACT-R (Acczent Tisse)
 - ACZ-R (Acczent Zen)
 - Thickness: 0.080" (2.0 mm)
 - Wear layer thickness: 32 mil (0.8mm)
 - Packaging: Available in 6' 6" (2 m) wide and approximately 76' linear feet (23 m) per roll

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Sheet material** meets ASTM F 1303, Type I, Grade 1, Class B performance sheet vinyl floorcovering with backing
- 2.2. **Heat Stability by Color Change** (ASTM F 1514): $\Delta E \leq 8$
- 2.3. **Light Stability by Color Change** (ASTM F 1515): $\Delta E \leq 8$
- 2.4. **Flexibility** (ASTM F 137): Passes
- 2.5. **Chemical Resistance** (ASTM F925): Passes
- 2.6. **Static coefficient of friction** (ASTM D 2047): ≥ 0.5 SCOF
- 2.7. **Static Load Limit** (ASTM F970): $250 \text{ psi} \leq 0.005''$
 - ***Modified 2000 psi:** $\leq 0.005''$
- 2.8. **Flammability** (ASTM E648): Class 1 ($\geq 0.45 \text{ W/cm}^2$)
- 2.9. **CAN/ULC S102.2:** FSR 165 / SDC 205

3. INSTALLATION

- 3.1. See Heterogeneous Sheet flooring installation instructions for complete details.
- 3.2. **Adhesives:**
 - **Tarkett 925 Adhesive Coverage:**
Porous Substrate: 250-300 sq. ft./gal.
Non-porous Substrate: 250-300 sq. ft. per gallon
 - **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
 - **Tarkett 996 Two-Part Epoxy Adhesive Coverage:**
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
 - **Tarkett RollSmart Adhesive Coverage:**
Porous & Non-porous Substrate: 350 - 400 sq. ft. per gallon
(3/8" Nap Paint Roller used with a paint tray)
 - **Tarkett Cold Weld Liquid:**
Approximate Coverage: 175 – 200 lin. ft. per 4.5 oz. tube

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Acczent Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com
Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. LIMITED WARRANTY

Limited 10-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

* Static loads greater than 250 psi fall outside of the scope of the ASTM F970 Test Method. Modified static load testing does not provide information related to the long-term exposure and the residual indentation of an installed floorcovering system which includes the subfloor, adhesive, underlayment, and cementitious patching/leveling compounds. Residual indentation(s) may remain visible in any resilient flooring installation, however, overhead lighting, natural lighting and the application of a gloss floor finish may increase the appearance.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com