

1. DETAILS

HDF-Board: No Added Formaldehyde
Thickness: 0.39" (10 mm)
Width: 7.64" (194mm)
Length: 50.87" (1292 mm)
Edges: Square
Wear Resistance: AC4
Indentation: IC2
Planks per Carton: 6
Square Feet per Carton: 16.18 (1.50 m²)
Weight per Carton (Lbs.): 33.1 lbs. (15.01 kg)
Cartons per Pallet: 28
Country of Origin: Germany
FloorScore® Certification: SCS-EC10.2-2007: Yes
Carb II Compliant: Yes

2. INSTALLATION - See package insert for complete Installation Information.

Use: Residential / Light Commercial
Installation System: T-Lock, Angle-Drop (5G)
Location: Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Tarkett laminate flooring shall acclimate to the temperature of the room. Place unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity shall be between 40% and 70%.
- Substrate shall be level to within 1/8" in 8 feet (3.18 mm in 2.4 m).
- Install approved laminate foam underlayment. Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 40' (12m) in length or width will require the use of Tarkett T-Molding.
- Planks are installed by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Position the plank so it is aligned with the short side of the previous plank. Rotate the plank downward to engage the long and short side joints.
- The first and last plank in each row shall be at least 12" (30.4 cm) in length. Stagger end joints a minimum of 12" (30.4 cm).



3. WARRANTY - See package insert for complete Warranty Information.

- LIFETIME LIMITED RESIDENTIAL WARRANTY
- 10 YEAR LIMITED LIGHT COMMERCIAL WARRANTY

4. CARE AND MAINTENANCE

- Post installation temperature must be maintained between 65°F and 85°F. Relative humidity must be maintained between 40% and 70%.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching, equip tables and chairs with proper floor protectors.
- To help prolong the life of the floor, use walk-off mats at outside entrances to collect dirt and debris and excess moisture.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wipe up all spills promptly with a dry cloth.
- When necessary, lightly damp mop floor with Tarkett SureShine Floor Cleaner or equal neutral floor cleaner. Do not use excessive water when cleaning.

