



Broccato #40030

Product Specification

| Face Construction | Imperial | Metric |
|-------------------------------|---|---------------------|
| Construction | Tufted Patterned Tipshear | |
| Tufted Pile Weight | 32.0 oz/sq yd | 1085 g/sq m |
| Gauge | 5/64 inch | 50.4 rows/10 cm |
| Stitches per Inch | 11.0 stitches / inch | 43.3 stitches/10 cm |
| Finished Pile Height | 0.197 inch | 5.0 mm |
| | 0.079 inch | 2.0 mm |
| Total Finished Weight | 103.7 oz/sq yd | 3515 g/sq m |
| Density | 8087 | |
| Kilotex | 21.0 | |
| Fiber System | Dynex SD® nylon | |
| Dye Method | Solution Dyed | |
| Pattern Repeat | 18.75" W x 30.91" L | 476 mm W x 785 mm L |
| Fluorine-Free Soil Protection | Eco-Ensure | |
| Primary Backing | Woven Polypropylene | |
| Backing Construction | ErgoStep® High Density Polyurethane Cushion | |
| Width | 12' 6" feet | 381 cm |
| Product Recycled Content | 9.4% overall recycled content | |

Product Testing/Information

| | | |
|----------------------|--|---|
| IAQ Results | CRI Green Label Plus Registration Number GLP7544. (Low VOC emitter.) | |
| Surface Flammability | Methenamine Pill | Meets CAN/CGSB-4.2 No. 27.6/DOC FF 1-70 |
| | Flooring Radiant Panel | ASTM E-648 Class 2 |
| | Smoke Density | ASTM E-662 Less than 450 |
| | Steiner Tunnel | ULC S102.2 Less than 300FS, 500SD |

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.

To achieve best results, more time should be allowed to install patterned carpet. This style has a definite pattern and must be installed according to pattern match procedures as outlined in Tarkett installation specifications, available from your Tarkett Representative.

Manufacturing tolerances on Tarkett tufted carpets are:

- Bow - 1" per 12' width
- Skew - 1" per 12' width
- Edge Straightness - +/- 1/2" variation
- Pattern Elongation - 1" per 10' length

For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.

Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.

Recommendations are available from your Tarkett Representative.

Warranties

- 10 Year Limited Abrasive Wear
- Lifetime Limited Anti-Static (Less than 3.5 kv)
- 10 Year Limited No Delamination or Edge Ravel
- 10 Year Limited Backing Resiliency

Product Notes

1. All specifications are subject to normal manufacturing tolerances.
2. Dyelots may vary from samples.
3. The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.
4. Tarkett reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

Tarkett North America

Technical Services Department
1000 Vista Drive
Dalton, GA 30721
800.248.2878 Fax 706.259.2136
info@tarkettna.com

www.tarkettna.com