

**1. PROPRIETARY PRODUCT/MANUFACTURER**

1.1. **Proprietary Product:** Luxury vinyl floor covering with Techtonic protection to deliver unmatched durability in high-traffic areas in a plank design. Suitable for commercial working environments and offices.

1.2. **Manufacturer:**  
Tarkett North America Phone: (800) 899-8916  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkett.com](http://www.tarkett.com)

**1.3. Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Collections Infinies is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 32 mil wear layer and state-of-the-art Techtonic protective finish for long term performance.

**1.3.2. Styles:**

- **Collections Infinies**
- **Wear layer Thickness:** 32 mil (0.8 mm)
- **Edge treatment:** Square Edge (SE)
- **Overall thickness:** .120" (3 mm)

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005''$
- 2.3. **Residual Indentation** (ASTM F1914): Passes
- 2.4. **Static coefficient of friction** (ASTM D2047):  $\geq 0.5$  SCOF
- 2.5. **Dimensional Stability** (ASTM F2199): Passes
- 2.6. **Resistance to Heat** (ASTM F1514):  $\Delta\Sigma \leq 8.0$
- 2.7. **Resistance to Light** (ASTM F1515):  $\Delta\Sigma \leq 8.0$
- 2.8. **Chemical Resistance** (ASTM F925): Passes
- 2.9. **Fire Performance, Critical Radiant Flux** (ASTM E648): Class 1 ( $> 0.45$  W/cm<sup>2</sup>)
- 2.10. **Smoke Density**(ASTM E648):  $\leq 450$

**3. INSTALLATION**

See Luxury Vinyl Plank installation instructions for complete details.

**3.1 Adhesives:**

- **Tarkett RollSmart Adhesive:**  
Coverage: 350 – 400 sq. per gallon  
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959 Vinyl Tile Adhesive Coverage:**  
Porous Substrate: 150-175 sq. ft. per gallon  
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 959HM High Moisture Substrate Adhesive**  
Porous Substrate: 125-150 sq. ft. per gallon  
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

**4. AVAILABILITY AND COST**

Available through authorized Tarkett distributors nationwide.

**5. MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Collections Infinies Maintenance Instructions for complete maintenance details.

**6. TECHNICAL SERVICES**

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)  
Contact Technical support at (800)-899-8916 or Email: [Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)  
**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

**7. WARRANTY**

Limited 25 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.



## Collections Infinies

## Product Specification

SIZE OPTIONS	6" x 36"	9" x 36"	12" x 36"	18" x 36"	18" x 18"
<b>Crystal Series</b>					
Clear Basalt	•			•	
<b>Dropcloth Series</b>					
Strato No.1, Strato No.2, Terra No.1, Terra No.2, Moss No.1, Moss No.2		•			•
<b>Faux Bois Series</b>					
Amarillo, Celeste, & Naranja	•	•			
<b>Glow Series</b>					
Pewter Portrait, Ballet Lightest Warm Grey	•				
<b>Meshwork Series</b>					
Tallow, Pumice			•		•
<b>Outliners Series</b>					
Caerulea, Mons, Tellus	•	•			•
<b>Riot Flora Series</b>					
Riot Multi, Riot Static Blue				•	•
<b>Trans Materia Series</b>					
Light Marble, Light Ribweave, Light Felt				•	•

EMBOSS OPTIONS	Frost (FR)	Quarry (QU)	Rough (RG)	Sawn (SW)	Tick (TK)	Pathway (PH)	Passage (PS)
<b>Collections Infinies® Series Abstract</b>							
Asphalt (PCAS)		•				S	
Broadcloth (PCBC)	•	S					
C-Stamped (PCCD)		•					S
Chenille (PCCH)	•	S					
Color Beam (PCBE)	•	S					
Color Pop (PCOP)	•	S					
Color Weave (PCWE)	•	S					
Faux Bois (PCFB)					S		
Filament (PCFI)					S		
Illusion (PCIN)	•	S					
NuGrain (PCNU)		•	•		S		
Outliners (PCOU)	•	S				•	
Rays (PCRS)	S	•			•		
Woven Reed (PCWR)	•	S					
Substrate (PCSU)	•	S					

**S** = Standard

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

### Tarkett North America

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
 info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)