

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Tarkett Contour Series Wood Stone Luxury vinyl floor covering with Techtonic™ protection to deliver unmatched durability in high-traffic areas in a plank design.
- 1.2. **Manufacturer:**
Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com
- 1.3. **Proprietary Product Description:**
- 1.4.1. **Construction:** Tarkett Contour is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 32-mil wear layer and state-of-the-art Techtonic™ protective finish for long term performance. Tarkett's Techtonic™ is a massive shift forward in performance for hard surface floors. Its advanced polyurethane technology is super tough, resisting scratching, abrasions, scuffing and staining.

1.3.1. Styles:

Contour Series Wood Stone

- **Finish:** Techtonic™
- **Wear layer Thickness:** 32 mil (0.8 mm)
- **Edge treatment:** Square Edge (SE)
- **Overall thickness:** .120" (3 mm)
- 11 Wood / 8 Stone Collections

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Flexibility** (ASTM F137): Passes
- 2.3. **Static Load Limit** (ASTM F970): 250 psi, $\leq 0.005''$
- 2.4. **Residual Indentation** (ASTM F1914): Passes
- 2.5. **Static coefficient of friction** (ASTM D 2047): ≥ 0.5 SCOF
- 2.6. **Dimensional Stability** (ASTM F2199): Passes
- 2.7. **Resistance to Heat** (ASTM F1514): $\Delta\Sigma \leq 8.0$
- 2.8. **Resistance to Light** (ASTM F1515): $\Delta\Sigma \leq 8.0$
- 2.9. **Chemical Resistance** (ASTM F925): Passes
- 2.10. **Fire Performance, Critical Radiant Flux** (ASTM E648): Class 1 (> 0.45 W/cm²)

3. INSTALLATION

See Contour Luxury Vinyl Plank installation instructions for complete details.

3.1 Adhesives:

- **Tarkett RollSmart Adhesive:**
Coverage: 350 – 400 sq. per gallon
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959 Vinyl Tile Adhesive Coverage:**
Porous Substrate: 150-175 sq. ft. per gallon
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 959HM High Moisture Substrate Adhesive**
Porous Substrate: 125-150 sq. ft. per gallon
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical support at (800)-899-8916 or Email: Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 25-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.



Contour Series Abstract

Product Specification

	STANDARD EMOSS	SIZES AVAILABLE					
		6x36	9x36	12x36	18x18	18x36	36x36
Asphalt (PCAS): Quarter Turn	Pathway				•		
Broadcloth (PCBC): Horizontal Ashlar, Quarter Turn, Vertical Ashlar	Quarry				•		
Chenille (PCCH): 6x36 Herringbone, Unidirectional 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar	Quarry	•			•		
C-Stamped (PCCD): 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x36 – Vertical Ashlar	Passage			•	•		
Color Play: Color Beam (PCBE), Color Pop (PCOP), Color Weave (PCWE) 6x36 – Herringbone, Unidirectional 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 9x36 – Vertical Ashlar	Quarry	•	•		•		
Filament (PCFI): 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 9x36 – Vertical Ashlar	Tick		•	•	•		
GeoGrid (PCGE): 6x36 – Herringbone, Unidirectional 18x18, 36x36 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x36, 18x36 – Vertical Ashlar	Pathway	•		•	•	•	•
Illusion (PCIN): 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 9x36, 12x36 – Vertical Ashlar	Quarry		•	•	•		
Rays (PCRS): 6x36 – Herringbone, Unidirectional 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x36 – Vertical Ashlar	Frost	•		•	•		
Substrate (PCSU): 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 9x36, 12x36 – Vertical Ashlar	Quarry		•	•	•		
Woven Reed (PCWR): 6x36 Herringbone, Unidirectional 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar	Quarry	•			•		

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com