

Tandus Centiva

# CONTOUR SERIES ABSTRACT

LUXURY VINYL TILE

---

## SPECIFICATIONS

|                              |   |
|------------------------------|---|
| <b>Classification:</b>       | ASTM F1700 Class III Type B   |
| <b>Total Thickness:</b>      | 0.120" (3.0 mm)   |
| <b>Wear Layer Thickness:</b> | 32 mil (0.76 mm)  |
| <b>Finish:</b>               | Techtonic™  |
| <b>Edge Treatment:</b>       | Square Edge (SE)  |
| <b>Emboss:</b>               | Standard shown on sample. For additional emboss options see product brochure. |
| <b>Warranty:</b>             | 20-Year Limited Commercial Wear Warranty                                      |
| <b>Colors:</b>               | 84  |

---

## TESTING

|                               |            |             |
|-------------------------------|------------|-------------|
| <b>Static Load:</b>           | ASTM F970  | Passes      |
| <b>Residual Indentation:</b>  | ASTM F1914 | Passes      |
| <b>Slip Resistance:</b>       | ASTM D2047 | ≥0.5 SCOF   |
| <b>Flammability:</b>          | ASTM E648  | ≥0.45 w/cm2 |
| <b>Smoke Density:</b>         | ASTM E662  | ≤450        |
| <b>Chemical Resistance:</b>   | ASTM F925  | Passes      |
| <b>Staining:</b>              | ASTM F925  | Passes      |
| <b>Resistance to Light:</b>   | ASTM F1515 | ΔE≤8        |
| <b>Resistance to Heat:</b>    | ASTM F1514 | ΔE≤8        |
| <b>Dimensional Stability:</b> | ASTM F2199 | Passes      |

---

## ENVIRONMENTAL DATA

|                           |  |
|---------------------------|--|
| <b>Materials:</b>         | No Heavy Metals; Non-Toulene Ink System  |
| <b>Indoor Air Quality</b> | Meets CDPH Standard Method v1.1-2010;  |
| <b>Recyclability:</b>     | FloorScore® Certification  |
| <b>LEED Scoreboard:</b>   | 100% Recyclable through our ReStart® Program<br>LEED 2009<br>MRc2 Construction Waste Management<br>MRc4 Recycled Content<br>MRc5 Regional Materials<br>IEQ 4.1 Low-Emitting Adhesives<br>IEQ 4.3 Low-Emitting Materials Flooring |

## LEED v4

MRc2 Building Product Disclosure and Optimization –  
Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization –  
Option 1 - Sourcing of Raw Materials  
Option 2 - Leadership Extraction Process  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials

For samples, warranties and more information, visit [tarkettna.com](http://tarkettna.com) or call 800.248.2878.



PRODUCT CERTIFIED FOR  
REDUCED ENVIRONMENTAL  
IMPACT. VIEW SPECIFIC  
ATTRIBUTES EVALUATED:  
UL COMFEL  
NSF 332



## SIZE OPTIONS

|                                 | 18" x 18" | 6" x 36" | 9" x 36" | 12" x 36" |
|---------------------------------|-----------|----------|----------|-----------|
| <b>Contour® Series Abstract</b> |           |          |          |           |
| Asphalt (PCAS)                  | •         |          |          |           |
| Broadcloth (PCBC)               | •         |          |          |           |
| C-Stamped (PCCD)                | •         |          |          | •         |
| Chenille (PCCH)                 | •         | •        |          |           |
| Color Beam (PCBE)               | •         | •        | •        |           |
| Color Pop (PCOP)                | •         | •        | •        |           |
| Color Weave (PCWE)              | •         | •        | •        |           |
| Faux Bois (PCFB)                |           | •        | •        |           |
| Filament (PCFI)                 | •         |          | •        | •         |
| Illusion (PCIN)                 | •         |          | •        | •         |
| NuGrain (PCNU)*                 |           | •        |          |           |
| Outliners (PCOU)                | •         | •        | •        |           |
| Rays (PCRS)                     | •         | •        |          | •         |
| Woven Reed (PCWR)               | •         | •        |          |           |
| Substrate (PCSU)                | •         |          | •        | •         |

\* Also available in plank sizes 4" x 36" and 6" x 48"

## EMBOSS OPTIONS

|                                 | Frost<br>(FR) | Quarry<br>(QU) | Rough<br>(RG) | Sawn<br>(SW) | Tick<br>(TK) | Pathway<br>(PH) | Passage<br>(PS) |
|---------------------------------|---------------|----------------|---------------|--------------|--------------|-----------------|-----------------|
| <b>Contour® Series Abstract</b> |               |                |               |              |              |                 |                 |
| Asphalt (PCAS)                  |               | •              |               |              |              | S               |                 |
| Broadcloth (PCBC)               | •             | S              |               |              |              |                 |                 |
| C-Stamped (PCCD)                |               | •              |               |              |              |                 | S               |
| Chenille (PCCH)                 | •             | S              |               |              |              |                 |                 |
| Color Beam (PCBE)               | •             | S              |               |              |              |                 |                 |
| Color Pop (PCOP)                | •             | S              |               |              |              |                 |                 |
| Color Weave (PCWE)              | •             | S              |               |              |              |                 |                 |
| Faux Bois (PCFB)                |               |                |               |              | S            |                 |                 |
| Filament (PCFI)                 |               |                |               |              | S            |                 |                 |
| Illusion (PCIN)                 | •             | S              |               |              |              |                 |                 |
| NuGrain (PCNU)                  |               | •              | •             |              | S            |                 |                 |
| Outliners (PCOU)                | •             | S              |               |              |              | •               |                 |
| Rays (PCRS)                     | S             | •              |               |              | •            |                 |                 |
| Woven Reed (PCWR)               | •             | S              |               |              |              |                 |                 |
| Substrate (PCSU)                | •             | S              |               |              |              |                 |                 |

**S** = Standard

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

## Tarkett North America

30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916

[tarkettna.com](http://tarkettna.com)

08/2018