

Tandus Centiva

CONTOUR SERIES WOOD STONE

LUXURY VINYL TILE

SPECIFICATIONS

Classification:	ASTM F1700 Class III Type B
Total Thickness:	0.120" (3.0 mm)
Wear Layer Thickness:	32 mil (0.76 mm)
Finish:	Techtonic™
Edge Treatment:	Square Edge (SE)
Emboss:	Standard shown on sample. For additional emboss options see product brochure.
Warranty:	20-Year Limited Commercial Wear Warranty
Colors:	WOOD - 50/STONE - 27

TESTING

Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Passes
Slip Resistance:	ASTM D2047	≥0.5 SCOF
Flammability:	ASTM E648	≥0.45 w/cm2
Smoke Density:	ASTM E662	≤450
Chemical Resistance:	ASTM F925	Passes
Staining:	ASTM F925	Passes
Resistance to Light:	ASTM F1515	ΔE≤8
Resistance to Heat:	ASTM F1514	ΔE≤8
Dimensional Stability:	ASTM F2199	Passes

ENVIRONMENTAL DATA

Materials:	No Heavy Metals; Non-Toulene Ink System
Indoor Air Quality	Meets CDPH Standard Method v1.1-2010;
Recyclability:	FloorScore® Certification
LEED Scoreboard:	100% Recyclable through our ReStart® Program LEED 2009 MRc2 Construction Waste Management MRc4 Recycled Content MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring

LEED v4

MRc2 Building Product Disclosure and Optimization –
Environmental Product Declarations
MRc3 Building Product Disclosure and Optimization –
Option 1 - Sourcing of Raw Materials
Option 2 - Leadership Extraction Process
MRc5 Construction and Demolition Waste Management
IEQc2 Low-Emitting Materials

For samples, warranties and more information, visit tarkettna.com or call 800.248.2878.



PRODUCT CERTIFIED FOR
REDUCED ENVIRONMENTAL
IMPACT: VIEW SPECIFIC
ATTRIBUTES EVALUATED:
UL GREENGUARD
NSF 332



EMBOSS OPTIONS

	Frost (FR)	Natural Grain (NG)	Quarry (QU)	Rough (RG)	Sawn (SW)	Tick (TK)
Antique Wood (PCAN)						
0383	•	S			•	•
3815, 3816	•		S			•
0351, 0353, 0357, 0359, 3512		•		S	•	•
0301, 0302, 0305, 0306, 3720		•		•	S	•
3810, 3811, 3812		•		•	S	•
Exotic Wood (PCEX)						
3205		S		•		•
3314		•		S		•
3210, 3213, 3214, 3302, 3310, 3311, 3312, 3324, 3625, 3901, 3301	•	•		•		S
Grand Ash (PCGA)						
3632, 3634, 3635		•		S		•
Modern Wood (PCMD)						
0361, 3306	•	S		•		•
3820, 3821, 3822	•		•	S		•
3823, 3824, 3825				S	•	
3602, 3604, 3606, 3610, 3732, 3104		•		•		S
NuGrain (PCNU)						
3710, 3712, 3715, 3717		•	•	•		S

	Fresco (FC)	Frost (FR)	Pathway (PH)	Quarry (QU)
Concrete (PCCN)				
0710, 0712, 0718	•		•	S
7241, 7243	•	•	S	•
Fossil Stone (PCFS)				
0830, 0834	•	•	•	S
Legacy Stone (PCLE)				
0553, 0557	•	•	S	•
0541		•	•	S
Modern Stone (PCMS)				
0604, 0606, 0610, 0612, 0614, 0616, 0620, 0624, 0630, 0631, 0632, 0633	•		•	S
Passageway (PCPA)				
0840, 0841, 0842			S	•
Vestige (PCVE)				
1018, 1019		•		S

S = Standard

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

SIZES

	12x24	18x18	36x36
Contour® Series Stone			
Concrete (PCCN)	•	•	•
Fossil Stone (PCFS)	•	•	
Legacy Stone (PCLE)	•	•	
Modern Stone (PCMS)	•	•	
Passageway (PCPA)	•	•	
Vestige (PCVE)	•	•	
	4x36	6x36	6x48
Contour® Series Wood			
Antique Wood (PCAN)	•	•	•
Exotic Wood (PCEX)	•	•	•
Grand Ash (PCGA)	•	•	•
Modern Wood (PCMD)	•	•	•
NuGrain (PCNU)	•	•	•

Other sizes available. For additional information contact your Tandus Centiva Account Executive.

Tarkett North America

30000 Aurora Road
Solon, Ohio 44139
800.899.8916

tarkettna.com

08/2018