



## Edge Guards

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Edge Guard Mouldings

1.2. **Manufacturer:**

Tarkett North America                      Phone:     (800) 899-8916  
30000 Aurora Rd.                                (440) 543-8916  
Solon, Ohio 44139  
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Edge Guard Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Edge Guard Mouldings are designed for interior applications only and not recommended for commercial kitchen environments.

1.3.2. **Styles:**

**EG-XX-G \***: 1-11/32" (3.41 cm) transition reducer with undercut for 5/16" (7.94 mm) glue down carpet, 2-3/8" (6.03 cm) base surface

**EG-XX-H \***: 1-9/32" (3.25 cm) transition reducer with undercut for 1/4" (6.35 mm) glue down carpet, 2-1/8" (5.40 cm) base surface

**EG-XX-J \***: 1-1/16" (2.70 cm) transition reducer with undercut for 3/16" (4.76 mm) glue down carpet, 1-3/4" (4.45 cm) base surface

**EG-XX-K:** Rounded top transition reducer with undercut for 1/4" (6.35 mm) carpet or artificial grass carpet, 1-5/8" (4.13 cm) base surface

**EG-XX-L:** Bevel-edge transition reducer with deep undercut for 5/16" (7.94 mm) carpet, 2" (5.08 cm) base surface

**EG-XX-W:** Bevel-edge transition reducer with undercut for 3/8" (9.53 mm) integral pad and carpet, 3" (7.62 cm) base surface

\* Complies with ADA requirements for changes in level.

1.3.3. **Physical Characteristics:**

Length: 12 ft. (3.66 m)

Packaging: 20 pieces [240 ft. (73.15 m)] per carton

**Note:** EG-XX-L packaged 25 pieces per carton, 300 ft. (91.44 m).  
EG-XX-W packaged 10 pieces per carton, 120' (36.58 m).

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance** (ASTM D 2047 Static Coefficient of Friction): Exceeds Federal Standards and ADA requirements of 0.5 SCOF for walking surfaces.

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux): Class 1

### 3. INSTALLATION

3.1. See Tarkett Resilient Moulding installation and maintenance instructions for complete details.

3.2. **Adhesives:**

**Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)

Application: Brush on T-Moulding and track on mitered corner areas

Approximate coverage:

1 Quart (0.95 liters) – 24 to 36 sq. ft.

1 Gallon (3.79 liters) – 100 to 150 sq. ft.

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.

#### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916 Ext. 9297 Fax 440.632.5643  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkettna.com](http://www.tarkettna.com)