


Wyndham

Details

Series / Sériés:	M9000
Wearlayer:	Urethane Sealed (Low Gloss)
Nominal Total Thickness:	.042" (1.07mm)
Nominal Wearlayer Thickness:	.006" (.15mm)
Widths:	12' (3.7m)
Maximum Roll Size:	144 SY (120.4 m ²)
Weight per Sq. Yd. (Lbs):	2.02 (0.92 kg)
ASTM E-648 Flooring Radiant Panel:	>0.45 W / cm ²
FloorScore® Certification SCS-EC10.3-2014:	SCS-FS-02746
Asthma & Allergy Certification:	Yes



Installation

Use:	Residential Resilient Sheet Flooring
Installation System:	Glueless or Full Spread.
Location:	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
Adhesive:	Tarkett QBond-One™
Adhesive Application:	Releasable - Apply adhesive evenly over substrate using a medium nap paint roller. Allow adhesive to dry until tacky to the touch. Permanent - Apply adhesive with a 1/32" deep x 1/16" wide x 1/32" apart notched trowel. Place flooring into adhesive immediately after application. When installing over an existing floor, allow adhesive to dry until it is tacky to the touch.
Seam Method:	Glueless-Double-cut dry , use Tarkett S875 Floating Seam Tape under seams on all approved substrates & Tarkett S860 Seam Tape over concrete. Full Spread (Releasable) - Double-cut. No tape required. Full Spread (Permanent) - Double-cut dry. Use Tarkett S860 Seam Tape.
Seam Sealer:	Tarkett DT-65 (Low Gloss)

- Maintain the work area, flooring and adhesive between 65° F and 85° F (18°C - 30°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Use only cementitious based patching and leveling compounds.
- Unroll flooring and allow material to relax for 10-20 minutes before fitting.
- When installing using the Glueless Installation System, leave a 1/4" space between flooring and all verticals (walls, pipes, cabinets, etc.).
- Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One™.
- When using the full spread application, roll flooring in both directions with a 75 lbs. (34 kg) 3-section floor roller.
- Protect sealed seams from all traffic for a minimum of 3 hours.

Maintenance

- When fully adhering, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations.
- Do not use felt pads.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.

Warranty

- 1 YEAR LIMITED WARRANTY, RESIDENTIAL USE
- Wear and Manufacturing Defects.