

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Event Series Luxury vinyl floor covering with Techtonic™ coating that delivers extreme durability and ease of maintenance in high traffic environments. Suitable for commercial working environments and office.

1.2. Manufacturer:

Tarkett North America Phone (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com
E-mail: info@tarkett.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Event Series is constructed with 30 mil wear layer reinforced with a Techtonic finish in numerous wood and stone patterns to provide an affordable, natural looking flooring that is stocked for faster turnaround times.

1.3.2. Styles:

- **Finish:** Techtonic
- **Wear layer thickness:** 30 mil (0.76 mm)
- **Edge treatment:** Square Edge (SE), optional Slight Bevel (SB)
- **Overall thickness:** 0.120" (3.0 mm)
- 32 Wood / 24 Stone patterns

2. PERFORMANCE AND TECHNICAL DATA

- 2.1 Meets ASTM F1700, Class III, Type B performance
- 2.2 **Static Load Limit** (ASTM F970): 250 psi, $\leq 0.005''$
- 2.3 **Residual Indentation** (ASTM F1914): Passes
- 2.4 **Static Coefficient of Friction** (ASTM D2047): SCOF ≥ 0.5
- 2.5 **Dimensional Stability** (ASTM F2199): Passes
- 2.6 **Resistance to Heat** (ASTM F1514): $\Delta\Sigma \leq 8.0$
- 2.7 **Resistance to Light** (ASTM F1515): $\Delta\Sigma \leq 8.0$
- 2.8 **Chemical Resistance** (ASTM F925): Passes
- 2.9 **Fire Resistance** (ASTM E648): CRF ≥ 0.45 watts/cm² NFPA, Class I
- 2.10 **CAN/ULC S102.2:** FSV 105 / SDV 340

3. INSTALLATION

3.1 See Tarkett Luxury Vinyl Plank installation instructions for complete details.

3.2 Adhesives:

- **Tarkett RollSmart Adhesive:**
Coverage: 350 – 400 sq. per gallon
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959HM High Moisture Substrate Adhesive**
Porous Substrate: 125-150 sq. ft. per gallon
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour/Event/Latitude/Resolve Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com
Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. LIMITED WARRANTY

Limited 20-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com