

Specification Sheet



Tarkett

THE ULTIMATE
FLOORING EXPERIENCE

Grande™ FiberFloor® Sheet Flooring

December 3, 2012

PRODUCT SPECIFICATIONS

| | |
|---|--|
| Series: | GR000 Series |
| Wearlayer: | Urethane (Low Gloss) |
| Nominal Wearlayer Thickness: | .020" (0.50mm) |
| Nominal Total Thickness: | .150" (3.75mm) |
| Widths: | 12' (3.6m) |
| Maximum Roll Size (Sq. Yds.): | 80 (66.8 m ²) |
| Weight per Sq. Yd. (Lbs.): | 5.1 (2.8 kg) |
| ASTM F-970 Static Load Limit: | 125 lbs/in ² (8.78 kg/cm ²) |
| ASTM F 1303: | Type I, Grade 2, Class C |
| HUD/FHA Minimum Property Standards: | Meets Wearlayer Thickness Requirement |
| FloorScore® Certification SCS-EC10.2-2007: | Yes |
| CERTIFIED asthma & allergy friendly™ | by the Asthma and Allergy Foundation of America (AAFA) |

INSTALLATION

| | |
|------------------------------|---|
| Use: | Residential. |
| Installation System: | Glueless or Full Spread. |
| Location: | Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors. |
| Adhesive: | Tarkett QBond-One™ Adhesive. |
| Adhesive Application: | Releasable - Apply adhesive evenly over substrate using a medium nap paint roller. Allow adhesive to dry until it is tacky to the touch. Permanent - Apply adhesive with a 1/32" deep x 1/16" wide x 1/32" apart notched trowel. Place flooring into adhesive immediately after application. When installing over an existing floor, allow adhesive to dry until it is tacky to the touch. |
| Seam Method: | Glueless - Double-cut dry. Use Tarkett S875 Floating Seam Tape under seams on all approved substrates. Tarkett S860 Seam Tape may be used when installing over concrete. Full Spread (Releasable) - Double-cut. No tape required. Full Spread (Permanent) - Double-cut dry. Use Tarkett S860 Seam Tape. |
| Seam Sealer: | Tarkett DT-65 Seam Sealer. |

- Maintain the work area, flooring and adhesive between 65°F and 100°F (18°C - 38°C) for 48 hours before, during and after installation. Maintain relative humidity is between 40% and 70%.
- Use only cementitious based patching and leveling compounds.
- Unroll flooring and allow material to relax for 20-30 minutes before fitting.
- When installing using the Glueless Installation System, leave a 1/4" space between flooring and all verticals (walls, pipes, cabinets, etc.).
- Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One™.
- When using the full spread application, roll flooring in both directions with a 75-100 lb. (34-45kg) sectional floor roller.
- Protect sealed seams from all traffic for a minimum of 3 hours.

CARE AND MAINTENANCE

- When adhering flooring, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.
- Use non staining mats or area rugs at doorways and entrances to collect excess water, sand, grit and debris.
- Maintain post installation temperature between 55° F and 100° F. Maintain relative humidity between 40% and 70%.

WARRANTY (refer to warranty guide for detailed information)

- Lifetime Wear and Manufacturing Defects.
- Lifetime Rip, Tear, Gouge and Indent.
- Lifetime Common Household Surface Stain.
- Lifetime Moisture Stain (Concrete only)
- Lifetime Underlayment Panel Stain.
- Lifetime Traffic/Asphalt Stain
- Lifetime Shoe Scuff



Tarkett

THE ULTIMATE
FLOORING EXPERIENCE