

## Details

<b>Wearlayer:</b>	.012"(.3mm)
<b>Nominal Thickness:</b>	.126"(3.2mm)
<b>Gloss:</b>	Matte
<b>Edge Treatment:</b>	Slight Microbevel
<b>Planks Per Carton:</b>	12
<b>Square Feet Per Carton:</b>	18.14
<b>Weight Per Carton:</b>	23.02
<b>Cartons Per Pallet:</b>	72
<b>ASTM F-925 Resistance to Chemicals:</b>	Pass
<b>ASTM F-1514 Heat Stability:</b>	$\Delta E < 8$
<b>ASTM F-1515 Light Stability:</b>	$\Delta E < 8$
<b>ASTM F-2199 Dimensional Stability:</b>	$< .020"$ (0.50mm)
<b>ASTM F-970 Static Load Limit:</b>	250 lbs/in <sup>2</sup> (113.4 kg)
<b>ASTM D-2047 Static Coefficient of Friction:</b>	$> 0.5$
<b>ASTM E-648 Floriing Radiant Panel:</b>	Class 1
<b>ASTM E-662 Smoke Density:</b>	$< 450$
<b>FloorScore® Certification SCS-EC10.2-2007:</b>	Yes



## Install

<b>Use:</b>	Residential and Light Commercial
<b>Installation System:</b>	Valinge 2G click system
<b>Location:</b>	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Maintain room temperature and flooring between 65° F and 85° F for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Cartons must be stored horizontally at all times.
- Use only cementitious based patching and leveling compounds.
- The substrate must be level within 1/8" in 10 ft and have no more than 1.3mm of deflection.
- Begin installation with the tongue side of the plank facing the starting wall.
- A minimum 1/4" (6.3mm) expansion space is required around the perimeter of the room and all vertical objects.
- Do not use a hammer and tapping block to install Transcend.
- The first and last plank in each row must be at least 12" (30.4cm) in length and offset end joints a minimum of 12" (30.4cm).

## Care and Maintenance

- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching and indentations, equip tables and chairs with proper floor protectors.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wipe up all spills promptly with a damp cloth or mop.
- Wash floor with Tarkett SureShine Floor Cleaner or equal neutral floor cleaner designed for vinyl flooring.
- The use of non-staining mats can remove dirt and debris in the entryways and help prolong the life of the floor.
- Maintain post installation temperature between 55° F and 100° F. Maintain relative humidity between 40% and 70%.

## Warranty

The following categories are covered for a residential usage with a 25 year limited warranty. Proof of purchase is required for claim submittal. Please refer to our Consumer Protection Guide on TarkettNA.com for complete information.

25 Year Residential Limited Warranty		7 Year Light Commercial Warranty
Wear and Manufacturing Defects	Rip, Tear, Gouge	Wear
Year Traffic/Asphalt Stain	Common Household Stain	Manufacturing Defects
Moisture Stain (Concrete Only)	Underlayment Panel Stain	