



**1. PROPRIETARY PRODUCT/MANUFACTURER**

- 1.1. **Proprietary Product:** Tarkett LinoFloor xf<sup>2</sup>™ homogeneous linoleum floorcovering, single layer on jute backing with xf<sup>2</sup>™ surface protection.
- 1.2. **Manufacturer:**  
Tarkett North America                      Phone:     (800) 899-8916  
30000 Aurora Rd.                                (440) 543-8916  
Solon, Ohio 44139  
Web: www.tarkett.com
- 1.3. **Proprietary Product Description:**
  - 1.3.1. **Construction:** Tarkett LinoFloor xf<sup>2</sup>™ consists of an homogeneous layer of oxidized linseed oil and natural resins mixed with wood or cork flour, limestone and pigments affixed to a jute backing. The marbled pattern extends evenly throughout the total thickness. Surface has xf<sup>2</sup>™ treatment for surface protection and reduced maintenance.
  - 1.3.2. **Styles:**
    - Etrusco, Originale, Elle, Emme, Trentino, & Veneto**
      - Thickness: 2.5 mm (0.098")
      - xf<sup>2</sup>™ Surface Protection
      - Weight/yd<sup>2</sup> (/m<sup>2</sup>): 5.35 lbs (2.9 kg)
      - Packaging - Available in 6' 6" (2 m) wide 65-100 linear feet(20-30 m) per roll.

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

- 2.1. Meets ASTM F 2034 – Type 1 performance standards for sheet linoleum floor covering
- 2.2. **Heat Stability by Color Change** (ASTM F1514):  $\Delta E \leq 8$
- 2.3. **Light Stability by Color Change** (ASTM F1515):  $\Delta E \leq 8$
- 2.4. **Flexibility** (ASTM F 137): Passes
- 2.5. **Chemical Resistance** (ASTM F925): Passes
- 2.6. **Static coefficient of friction** (ASTM D2047):  $\geq 0.5$  SCOF
- 2.7. **Static Load Limit** (ASTM F970):  $\leq 0.005$ " residual indentation (150 psi load)
- 2.8. **Flammability** (ASTM E648/CRF):  $\geq 0.45$  W/cm<sup>2</sup> (Class 1)
- 2.9. **Smoke Development** (ASTM E662):  $\leq 450$
- 2.10. **CAN/ULC S102.2:** FSR 100 / SDC 225

**3. INSTALLATION**

- 3.1. See LinoFloor xf<sup>2</sup>™ sheet installation instructions for complete details.
- 3.2. **Adhesives:**
  - **Tarkett 965 Coverage:**  
Porous Substrate: 125-150 sq. ft./gal.  
Non-porous Substrate: 125-150 sq. ft./gal.
  - **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**  
Porous & Non-porous Substrate: 150-175 sq. ft. per gallon
  - **Tarkett 996 Two-Part Epoxy Adhesive Coverage:**  
Porous & Non-porous Substrate: 150-175 sq. ft. per gallon

**4. AVAILABILITY AND COST**

Available through authorized Tarkett distributors nationwide.

**5. MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to LinoFloor xf<sup>2</sup> Linoleum sheet maintenance Instructions for complete maintenance details.

**6. TECHNICAL SERVICES**

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)

Contact Technical support at (800)-899-8916 or Email: [Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

**7. WARRANTY**

Limited 10-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

**Tarkett North America**

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
info@tarkettna.com  
[www.tarkett.com](http://www.tarkett.com)