

Specification Sheet



Tarkett

THE ULTIMATE FLOORING EXPERIENCE

Media™

FiberFloor® Sheet Flooring

December 3, 2012

PRODUCT SPECIFICATIONS

Series:	M0XXX
Wearlayer:	Urethane (Low Gloss)
Nominal Wearlayer Thickness:	.010" (0.25mm)
Nominal Total Thickness:	.080" (2.0mm)
Widths:	12' (3.6m)
Standard Roll Size (Sq. Yds.):	88 (73 m ²)
Weight per Sq. Yd. (Lbs.):	3.0 (1.6 kg)
ASTM F-970 Static Load Limit:	75 lbs/in ² (5.27 kg/cm ²)
ASTM F 1303:	Type I, Grade 3, Class C
HUD/FHA Minimum Property Standards:	Meets Wearlayer Thickness Requirement
FloorScore® Certification SCS-EC10.2-2007:	Yes
CERTIFIED asthma & allergy friendly™ by the Asthma and Allergy Foundation of America (AAFA)	

INSTALLATION

Use:	Residential.
Installation System:	Glueless or Full Spread.
Location:	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
Adhesive:	Tarkett QBond-One™ Adhesive.
Adhesive Application:	Releasable - Apply adhesive evenly over substrate using a medium nap paint roller. Allow adhesive to dry until it is tacky to the touch. Permanent - Apply adhesive with a 1/32" deep x 1/16" wide x 1/32" apart notched trowel. Place flooring into adhesive immediately after application. When installing over an existing floor, allow adhesive to dry until it is tacky to the touch.
Seam Method:	Glueless - Double-cut dry. Use Tarkett S875 Floating Seam Tape under seams on all approved substrates. Tarkett S860 Seam Tape may be used when installing over concrete. Full Spread (Releasable) - Double-cut. No tape required. Full Spread (Permanent) - Double-cut dry. Use Tarkett S860 Seam Tape.
Seam Sealer:	Tarkett DT-65 Seam Sealer.

- Maintain the work area, flooring and adhesive between 65°F and 100°F (18°C - 38°C) for 48 hours before, during and after installation. Maintain relative humidity is between 40% and 70%.
- Use only cementitious based patching and leveling compounds.
- Unroll flooring and allow material to relax for 20-30 minutes before fitting.
- When installing using the Glueless Installation System, leave a 1/4" space between flooring and all verticals (walls, pipes, cabinets, etc.).
- Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One™.
- When using the full spread application, roll flooring in both directions with a 75-100 lb. (34-45kg) sectional floor roller.
- Protect sealed seams from all traffic for a minimum of 3 hours.

CARE AND MAINTENANCE

- When adhering flooring, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.
- Use non staining mats or area rugs at doorways and entrances to collect excess water, sand, grit and debris.
- Maintain post installation temperature between 55° F and 100° F. Maintain relative humidity between 40% and 70%.

WARRANTY (refer to warranty guide for detailed information)

- 10 Year Wear and Manufacturing Defects.
- 10 Year Rip, Tear, Gouge and Indent.
- 10 Year Common Household Surface Stain.
- 10 Year Moisture Stain (Concrete only).
- 10 Year Underlayment Panel Stain.
- 10 Year Traffic/Asphalt Stain
- 10 Year Shoe Scuff



Tarkett

THE ULTIMATE FLOORING EXPERIENCE