



FiberFloor™ Moxie™

Product Specifications

1. **PROPRIETARY PRODUCT**

Fiberglass reinforced for stability and a polyurethane reinforced finish makes this product durable and easy to maintain.

Recommended areas for use: Residential

2. **PRODUCT DETAILS**

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** 24000
- **Overall thickness:** .125" (0.31 mm)
- **Wear Layer Thickness:** .012" (0.31 mm)
- **Widths:** 12' (3.6m)
- **Maximum Roll Size:** 104 SY (87 m²)
- **Weight per Square Yard:** 3.69 (1.67 kg)

3. **PRODUCT PERFORMANCE AND TECHNICAL DATA**

3.1. **Sheet Material:** ASTM F 1303, Type I, Grade 3, Class C

3.2. **Flooring Radiant Panel:** ASTM E648, >0.45 W/cm² 3.3.

Smoke: ASTM E662, <450

3.4. **HUD/FHA Minimum Property Standards:**
Meets Wearlayer Thickness

3.5. **FloorScore® Certification SCS-EC10.3-2014:** SCS-FS-02746

3.6. **Asthma and Allergy Certified:** (ASR-1155-03)

4. **ADHESIVE**

Tarkett QBond-One Adhesive

Releasable - Medium Nap Roller

Permanent - 1/32" x 1/16" x 1/32" trowel

Tarkett 959 Vinyl Tile and Plank Adhesive

Permanent - Porous: 1/16" x 1/16" x 1/16" V-notch

Non-porous: 1/32" x 1/16" x 1/32" U-notch

Porous/Non-porous: Medium Nap Roller

Follow Instructions on the Adhesive Label.

5. **INSTALLATION – Refer to Detailed Instructions at www.tarkettna.com**

- Installation System: Floating or Full Spread.
- Maintain the work area, flooring and adhesive between 55° F and 95° F (12.8°C - 35°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One or 959 Vinyl Tile and Plank Adhesive.
- Seal and protect seams from all traffic for a minimum of 3 hours.

6. **SEAM METHOD**

Glueless-Double-cut dry, use Tarkett S875 Floating Seam Tape under seams on all approved substrates & Tarkett S860 Seam Tape over concrete only.

Full Spread (Releasable) - Double-cut. No tape required.

Full Spread (Permanent) - Double-cut dry. Use Tarkett S860 Seam Tape.

7. **SEAM SEALER:** Tarkett DT-65 (Low Gloss)

8. **WARRANTY – For complete details, contact Tarkett Technical Services or go to www.tarkettna.com**


- 10 YEAR LIMITED RESIDENTIAL WARRANTY

9. **CARE AND MAINTENANCE**

- When fully adhering, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temp. between 55° F and 95° F (12.8°C - 35°C). Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner.

7. **TECHNICAL SERVICES**

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8275.



Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

888-639-8275 Fax 440-498-0025

northamerican.technicalsupport@tarkett.com

www.tarkettna.com

© 2019 Tarkett USA Inc. 06.17.19