



NuGen™ Glue Down

Product Specification

NuGen™ Glue Down flooring can be installed in Residential and Light-Commercial applications by following the recommendations outlined in the Tarkett NuGen™ Glue Down Installation Instructions at www.tarkettna.com

1. PRODUCT DETAILS

- **Nominal Thickness:** 0.142" (3.6 mm)
- **Wearlayer Thickness:** 0.012" (.51 mm)
- **Edge Treatment:** Square

	7"x48" 178mm x 1220 mm
Number of Styles	10
Square Feet per Carton	29.31 (2.72m ²)
Planks per Carton	12
Cartons per Pallet	55
Lbs. per Carton	39.47

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Dimensional Stability:** ASTM F2199: Passes
- 2.2. **Heat Stability:** ASTM 1514: $\Delta E \leq 8$
- 2.3. **Light Stability:** ASTM F1515: $\Delta E \leq 8$
- 2.4. **Residual Indentation :** ASTM F1914: Passes
- 2.5. **Stain Resistance:** ASTM F925: Passes
- 2.6. **Impact Sound:** ASTM E2179: $\Delta IIC \geq 22$ dB
- 2.7. **Slip Resistance:** ASTM D2047: SCOF ≥ 0.5
- 2.8. **Fire Performance:** ASTM E648: ≥ 0.45 w/cm²
- 2.9. **FloorScore® Certification SCS-EC10.3-2014 v4.0:** SCS-FS-04739

3. INSTALLATION – Refer to Detailed Installation

Instructions at www.tarkettna.com

- Maintain the work area temperature between 65° F and 85° F (12°C - 35°C) and ambient relative humidity between 40%-60% for 48 hours before, during and after installation.
- Cartons must be stored horizontally on a flat, sturdy base at all times.
- Use Tarkett Q-Bond One Adhesive, follow the instruction on the label.

4. WARRANTY –For complete details, contact Tarkett Technical Services or go to www.tarkettna.com

- LIFETIME RESIDENTIAL LIMITED WARRANTY
- 10-Year LIMITED LIGHT COMMERCIAL
- **Tarkett Qbond ONE** is the recommended adhesive when installing this flooring product. Issues associated with the use of non-recommended adhesives (including peaking, gapping, adhesion, bubbling, discoloration, indentation, etc.) are excluded from Tarkett's limited warranty. See complete Limited Warranty and Installation Instructions for details.

5. MAINTENANCE

- 5.1. Furniture can be replaced 24 hours after installation.
- 5.2. Never slide heavy furniture or appliances across the floor. Place sheets of plywood over finished floor when moving furniture and appliances into position.
- 5.3. Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- 5.4. Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- 5.5. Clean floor using Tarkett SureShine® Floor Cleaner or an equivalent pH neutral floor cleaner 48 hours after installation. Follow manufacturers label instructions for precaution and use.

7. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8297.



Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275 Fax 440-498-0025
northamerican.technicalsupport@tarkett.com

www.tarkettna.com