



Prima Marbleized and Olio

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Rubber Prima Marbleized and Olio Rubber Tiles, A.D.A. Compliant.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkett.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Prima Marbleized and Prima Olio Rubber Flooring System components are manufactured from a homogeneous composition of 100% synthetic rubber, high quality additives, and colorants to meet the performance requirements of ASTM F 1344, Class 1-B Standard Specification for Rubber Floor Tile and ASTM F-2169, Type TS, Class 1 and 2, Group 1 and 2 Standard Specification for Resilient Stair Treads.

All Tarkett Prima Marbleized and Prima Olio Rubber Flooring System components are designed for interior applications only and not recommended for environments where the product will be exposed to animal fats, vegetable oils, or petroleum based materials. (i.e.: commercial kitchens).

Note: This unique marbleization process will vary in density from tile to tile, as well as, product to product.

1.3.2. **Styles:**

SMOOTH (PRIMA) – Smooth texture surface, Marbleized design rubber floor tile, available in 2 mm (.080”) and 1/8” (3.2 mm) thickness

PRIMA HAMMERED (HRTP) – Hammered surface texture, Marbleized design rubber floor tile, available in 2 mm (.080”) and 1/8” (3.2 mm) thickness

PRIMA RICE PAPER (FRPAP) – Rice Paper surface texture, Marbleized design rubber floor tile, available in 2 mm (.080”) and 1/8” (3.2 mm) thickness

OLIO SMOOTH (Olio Smooth) Smooth texture surface, Olio design rubber floor tile, available in 2 mm (.080”) and 1/8” (3.2 mm) thickness

OLIO HAMMERED (HRTPO) – Hammered texture surface, Olio design rubber floor tile, available in 2 mm (.080”) and 1/8” (3.2 mm) thickness

OLIO RICE PAPER (FRPAPO) Rice Paper texture surface, Olio design rubber floor tile, available in 2 mm (.080”) and 1/8” (3.2 mm) thickness

1.3.3. **Physical Characteristics:**

Tile Size and Packaging:

- 12" x 12" x 1/8" (3.2 mm) thickness, 40 tiles per carton, 40 sq. ft. (3.7 sq. m.), 40 lbs/carton
- 12" x 12" x 0.80" (2 mm) thickness, 60 tiles per carton, 60 sq. ft. (5.6 sq m), 45 lbs/carton

NOTE: Prima also available in stair treads, risers, and stringers as a special order and are not returnable.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Hardness:** ASTM D 2240, Not less than 85 Shore A

2.2. **Abrasion Resistance:** ASTM D 3389 < 1.00 gram weight loss

2.3. **Slip Resistance:** ASTM D 2047 Meets or Exceeds a static coefficient of friction of 0.8

2.4. **Color Heat Stability:** ASTM F 1514 < 8.0 ΔE

2.5. **Acoustical:** ASTM E 492 - Impact Insulation Class (IIC) – 35 IIC for 0.080" (2mm) thickness and 40 IIC for 1/8" thickness

2.6. **Static Load Limit:** ASTM F 970 – Residual indentation passes at 0.005" or less with 250 PSI

2.7. **Chemical Resistance:** Passes

2.8. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux), Class 1

2.9. **Chemical Resistance:** Passed after 24 hours exposure to -5% Acetic acid, 70% Isopropyl alcohol, Sodium hydroxide solution (5% NaOH), Hydrochloric acid solution (5% HCl), Sulfuric acid solution (5% H₂SO₄), Household ammonia solution (5% NH₄OH), Household bleach (5.25% NaOCl), Disinfectant cleaner (5% active phenol)

2.10. **CAN/ULC S102.2:** FSR 45 / SDR 265

3. INSTALLATION

See rubber tile flooring installation instructions for complete details.

3.1. **Adhesives:**

• **Tarkett 965 Adhesive Coverage:**

Porous Substrate: 125-150 sq. ft. per gallon
Non-porous Substrate: 150-175 sq. ft. per gallon

• **Tarkett 996 Two-Part Epoxy Adhesive Coverage:**

Porous & Non-porous Substrate: 150-175 sq. ft. per gallon

• **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**

Porous & Non-porous Substrate: 150-175 sq. ft. per gallon

• **Tarkett 901 SpraySmart Adhesive Coverage:**

Porous & Non-porous Substrate: 80 sq. ft. per can (480 sq. ft. per carton)

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Rubber Tile maintenance instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical Support at (800) 899-8916 or E-mail:

Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916

info@tarkettna.com

www.tarkett.com