

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product** ProSheet™ Plus 3 (PS+3) eliminates the need for underlayment panels over properly constructed wood subfloors and provides a floating floor system. PS+3 underlayment is installed underneath glue down, click and floating Luxury Vinyl Tile and Plank, and loose laid resilient Sheet Flooring. PS+3 will minimize the effects of subfloor conditions such as staining and telegraphing of subfloor texturing.

Note: ProSheet™ Plus 3 is not recommended for use with heavy rolling loads.

1.2. Manufacturer:

Tarkett Phone: (800) 899-8916
 30000 Aurora Rd. Fax: (440) 543-8916
 Solon, Ohio 44139 Tech: (888)-639-8275
 Web: www.tarkettna.com

1.2.1. Construction: Felt with gel

1.2.2. Product Details:

| Series 97500 Large Roll | |
|-------------------------|---|
| Product Number: | 97501 |
| SAP | 220095001 |
| UPC: | 033799332755 |
| Length: | 132' (40.2m) |
| Width: | 6' (1.82m) |
| Diameter | 8.8" (22.35cm) |
| Coverage per roll: | 792 ft ² / 88 yd ² (73.6 m ²) |
| Weight per roll: | 139 lbs. (63 kg) |

| Series 97600 Small Roll | |
|-------------------------|---|
| Product Number: | 97601 |
| UPC: | 033799340668 |
| Length: | 33.34' (10.2m) |
| Width: | 6' (1.82m) |
| Diameter: | 5'6" (14.22cm) |
| Coverage per roll: | 200 ft ² / 22.23 yd ² (18.58 m ²) |
| Weight per roll: | 35 lbs. (26.30 kg) |
| Pallet quantity | 48 rolls |
| Pallet weight/dimension | 1,695lbs / 48"x74"x42" |

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. Physical Characteristics:

- Thickness: .030"
- Color: White

2.2. Acoustical Data:

- ASTM E2179: Delta IIC 7

3. INSTALLATION

- ProSheet™ Plus 3 is approved for installation over many types of substrates including concrete, plywood (single and double layer construction), OSB, Gypsum, and many existing floor coverings. Refer to the Tarkett ProSheet™ Plus 3 installation instructions for complete details regarding proper substrate type and preparation methods.
- ProSheet™ Plus 3 can be installed above grade, on grade and below grade over properly prepared concrete. Concrete must not exceed 75% RH in accordance with ASTM F2170, or 3 lbs MVER in accordance with ASTM F1869, and pH between 7 to 9.
- See Tarkett ProSheet™ Plus 3 installation instructions for complete details.

4. WARRANTY

One (1) year Limited Residential Warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

5. MAINTENANCE

Refer to the finished Tarkett flooring products installation instructions for complete maintenance details.

6. TECHNICAL SERVICES

Technical Services: For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8297.