

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Reducer Mouldings – All reducers are A.D.A. Compliant.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Reducers are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. All Reducer comply with A.D.A. requirements of Changes in Level. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Reducer are designed for interior applications only and not recommended for commercial kitchen environments.

1.3.2. **Styles:**

CRS-XX-A: 1/4" (6.35 mm) butt-to reducer with 1-1/2" (3.81 cm) taper, 12 ft. (3.66 m) lengths - 120 ft. (36.58 m) per carton

CRS-XX-B: 3/8" (9.53 mm) butt-to reducer with 1-1/2" (3.81 cm) taper, 12 ft. (3.66 m) lengths - 120 ft. (36.58 m) per carton

CRS-XX-D: 1/2" (12.7 mm) butt-to reducer with 2" (5.08 cm) taper, 12 ft. (3.66 m) lengths - 120 ft. (36.58 m) per carton

SSR-XX-B: Binder bar edging for 1/16" to 1/8" thick materials, 35 ft. (10.67 m) coils, 70 ft. (21.34 m) per carton

SSR-XX-D: 0.080" (2 mm) to 1/8" (3.17 mm) butt-to transition with 1-1/2" (3.81 cm) taper, 12 ft. (3.66 m) lengths, 300 ft. (91.4 m) per carton

RRS-XX-B: .080" (2.03 mm) reducer with 1-1/8" (2.86 cm) taper, 3 ft. (.91 m) lengths - 150 ft. (45.72 m) per carton

RRS-XX-C: 1/8" (3.18 mm) butt-to reducer with 1-1/4" (3.18 cm) taper, 3 ft. (.91 m) lengths - 150 ft. (45.72 m) per carton

RRS-XX-D: 1/8" (3.18 mm) butt-to reducer with 1-1/4" (3.18 cm) taper, 25 ft. (7.62 m) coils - 100 ft. (30.48 m) per carton

RIR-40-E: 3/8" (9.53 mm) **Replay™ Interlocking reducer**, 3.86" (9.80 cm) wide taper, 4 ft. (1.22 m) lengths

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations

- **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux): Class 1

3. INSTALLATION

3.1. See Tarkett Reducer installation instructions for complete details.

3.2. **Adhesives:**

Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)

Application: Brush on T-Moulding and track on mitered corner areas

Approximate coverage:

1 Quart (0.95 liters) – 24 to 36 sq. ft.

1 Gallon (3.79 liters) – 100 to 150 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year limited warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916 Ext. 9297 Fax 440.632.5643
info@tarkettna.com

www.tarkettna.com