



1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Replay Rubber Multi-functional and Sports Flooring Designed Specifically for Weight Room, Aerobic, and other high impact applications. Skate and spike resistant product.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Replay Rubber Multi-functional and Sports Flooring are manufactured from a composition of recycled truck tire crumb rubber encapsulated in a urethane binder. This unique construction creates a tough, abrasion and impact resistant composition with excellent slip-resistant, fatigue, and acoustical characteristics.

Tarkett Replay Rubber Multi-functional and Sports Flooring is designed for interior applications only and not recommended for environments where the product will be exposed to animal fats, vegetable oils, or petroleum based materials. (i.e.: commercial kitchens)

1.3.2. **Styles:**

Replay Commotion Sheet Flooring

- **COMR-XXX:**
1/4" (6.35 mm) thick, 4 ft (1.22 m) wide by 75 ft (22.86 m) rolls;
1.33 lbs /ft² (.603 kg/ft²)

3/8" (9.5 mm) thick, 4 ft (1.22 m) wide by 50 ft (15.24 m) rolls; 2.0
lbs /ft² (.907 kg/ft²)

Replay Commotion Square Edge Glue-Down Tile

- **COMT-XXX:**
3/8" (9.5 mm) thick; 24" x 24" (61 cm x 61 cm), Approximately 2.0
lbs /ft² (.907 kg/ft²)

Interlocking Commotion Loose-Lay Tile (No adhesive required)

- **COMI-XXX:**
3/8" (9.5 mm) thick, 24" x 24" (61 cm x 61 cm), Approximately 9.5
lbs (4.3 kg) per tile

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- **Hardness** (ASTM D 2240): 65 Shore A
- **Slip Resistance** (ASTM D-2047): Minimum 0.5 SCOF

- **Acoustical** (ASTM E492 Impact Insulation Class): 60 IIC
- **Static Load Limit:** ASTM F 970 – Passes at 250 PSI
- **Abrasion:** ASTM D-3389 < 1.00 gram weight loss
- **Chemical Resistance:** ASTM F-925 – 5% Acetic Acid, 70% Isopropyl Alcohol, 5% Sodium Hydroxide, 5% Hydrochloric Acid, 5% Ammonia, Bleach, 5% Phenol, and Sulfuric Acid.

3. INSTALLATION

3.1. See Replay tile, Interlocking tile or sheet rubber flooring installation instructions for complete details.

3.2. **Adhesives:**

- **Tarkett 965 Adhesive Coverage:**
Porous Substrate: 75-100 sq. ft. per gallon
Non-porous Substrate: 75-100 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**
Porous & Non-porous Substrate: 150-175 sq. ft. per gallon
- **Tarkett 901 SpraySmart Adhesive Coverage:**
Porous & Non-porous Substrate: 80 sq. ft. per can (480 sq. ft. per carton)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Replay maintenance instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com
Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com