



## Slim Line Transitions

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

#### 1.1. Proprietary Product: Slim Line Transitional Mouldings

#### 1.2. Manufacturer:

Tarkett North America                      Phone:     (800) 899-8916  
30000 Aurora Rd.                                (440) 543-8916  
Solon, Ohio 44139  
Web: www.tarkettna.com

#### 1.3. Proprietary Product Description:

1.3.1. **Construction** Tarkett Slim Line Transitions are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Tarkett transitions are designed for interior applications only.

#### 1.3.2. Styles:

**SLT-XX-A \***: 1/4" (6.35mm) carpet to 1/8" (3.18mm) resilient materials, 5/8" (1.59cm) cap with 11/64" (3.18mm) wide support, specify the **SLTC-XX-A** for contoured transition

**SLT-XX-B \***: .080" (2mm) resilient materials to 1/8" (3.18mm) resilient materials, 5/8" (1.59cm) cap with 11/64" (4.37mm) wide support, specify the **SLTC-XX-B** for contoured transition

**SLT-XX-C \***: .080" (2mm) resilient materials to 1/4" (6.35mm) materials, 5/8" (1.59cm) cap with 11/64" (3.18mm) wide support, specify the **SLTC-XX-C** for contoured transition

**SLT-XX-F \***: 1/4" (6.35mm) resilient materials to 3/8" (9.53mm) resilient materials, 1/4" (6.35mm) cap with 1/8" (3.18mm) wide support, specify the **SLTC-XX-F** for contoured transition

**SLT-XX-G \***: 1/4" (6.35mm) resilient materials to 1/2" (12.7mm) resilient materials, 1/4" (6.35mm) cap with 1/8" (3.18mm) wide support, specify the **SLTC-XX-G** for contoured transition

**SLT-XX-H**: 1/4" (6.35mm) resilient materials to .080" (2mm) resilient materials, 5/8" (15.9mm) cap with 5/32" (4mm) wide support, specify the **SLTC-XX-H** for contoured transition.

**SLT-XX-J \***: .080" (2mm) resilient materials to the floor with a 1/2" (12.7mm) cap, specify the **SLTC-XX-J** for contoured transition

**SLT-XX-L**: 1/4" (6.35mm) resilient materials to the floor with a 5/8" (15.9mm) cap, specify the **SLTC-XX-L** for contoured transition.

\* Complies with ADA requirements for changes in level.

#### 1.3.3. Physical Characteristics:

**Length:** 12 ft (3.66m)

**Packaging:** 25 pcs/carton

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

### 3. INSTALLATION

3.1. See Tarkett Resilient Moulding installation and maintenance instructions for complete details.

#### 3.2. Adhesives:

**Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)

Application: Brush

Approximate coverage:

1 Quart (0.95 liters) – 24 to 36 sq. ft.

1 Gallon (3.79 liters) – 100 to 150 sq. ft.

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.

## Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916 Ext. 9297 Fax 440.632.5643  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkettna.com](http://www.tarkettna.com)